

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive
Technical
DATA
BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

164, V6 24V Cloverleaf

1994 to 1997

Type		064.304. 95 ►: AR64.308 172kW
Capacity (cm³) / number of cylinders		2959 / 6
Compression ratio / pressure	bar	10.0 / _
Oil pressure	bar	[3.9 to 5.9]
Oil temperature	°C	90
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-4-2-5-3-6
No 1 cylinder position		FR
Thermostat opening temperature	°C	87±2. 95 ►: 83±2
Radiator cap pressure	bar	0.90 to 1.10

Fuel system

164, V6 24V Cloverleaf

1994 to 1997

Idle speed - manual [auto]	rpm	600 to 800. 95 ►: 650 to 750
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	_
HC @ idle speed [3000 rpm] - see page VI	ppm	_
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		_Bosch
Type / ref		ML1.7-Motronic
Main jet / needle		_
Injection pressure	bar	2.8 to 3.2
Pump pressure	bar	2.8 to 3.2
Octane rating	RON	95[U]

Ignition system

164, V6 24V Cloverleaf

1994 to 1997

Type		Direct electronic
Ignition coil		1 per cylinder
Primary resistance	ohms	_
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		_
Points gap (air gap)	mm	_
Dwell angle	° (%)	Computer control
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum		
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		NGK
Type		RPFR6B
Electrode gap	mm	N/A

Electrical system

164, V6 24V Cloverleaf

1994 to 1997

Battery	V / CC / RC	12 / 60Ah
Alternator voltage / full load current / engine rpm		14.3 to 14.8 / 120 / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear

164, V6 24V Cloverleaf

1994 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	205/55x16
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.2 / 2.0
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0±1.0. 95 ►: -1.0±1.0
Camber		-1°37'±20'
Castor		+2°17'±20'
King pin inclination		_

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+5.0±1.0
Camber		-1°±20'. 95 ►: -15'±20'

Torque wrench settings

164, V6 24V Cloverleaf

1994 to 1997

Cylinder head - stage 1	Nm	25
- stage 2	Nm	+240°
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	46 to 51
Main bearings	Nm	84 to 93
Clutch cover	Nm	20 to 25
Flywheel [driveplate]	Nm	113 LkC
Front hubs	Nm	66 to 73 + 61±2°
Rear hubs	Nm	250 to 300
Wheel nuts / bolts	Nm	95 to 105
Spark plugs	Nm	25 to 34

Capacities

164, V6 24V Cloverleaf

1994 to 1997

Engine oil & filter	litres	7.5
Gearbox - 4-speed [5-speed]	litres	1.8
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	13.0. Refill: 9.5
Fuel tank	litres	70

Notes and Illustrations

