

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

33, 1.5

1990 to 1992

Type		307.34 SOHC (77kW)
Capacity (cm ³) / number of cylinders		1490 / 4
Compression ratio / pressure	bar	9.5 / 10.3
Oil pressure	bar	1.2 to 2.8
Oil temperature	°C	90
Valve clearance - inlet	mm	0.35 to 0.40
Valve clearance - exhaust	mm	0.45 to 0.50
Firing order		1-3-2-4
No 1 cylinder position		FR
Thermostat opening temperature	°C	84 to 88
Radiator cap pressure	bar	0.9 to 1.1

Fuel system

33, 1.5

1990 to 1992

Idle speed - manual [auto]	rpm	850 to 1000
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤300
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Weber/Dellorto
Type / ref		W: 2x40IDF84/5. D: DRLA40FD/S
Main jet / needle		135
Injection pressure	bar	—
Pump pressure	bar	0.18 to 0.30
Octane rating	RON	98[E 95 RON]

Ignition system

33, 1.5

1990 to 1992

Type		Electronic
Ignition coil		Bosch
Primary resistance	ohms	0.7 to 1.0
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	12.0
Distributor		—
Points gap (air gap)	mm	[0.40 to 0.50]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	8±1 BTDC @ 900 (1st mark)
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	34 BTDC @ 4500 (2nd mark)
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	0 @ 500 to 600
	° Crankshaft @ rpm	19 to 24 @ 3000
	° Crankshaft @ rpm	22 to 26 @ 6000
Vacuum range check	mbar	150 to 400
Maximum vacuum advance	° Crankshaft	11 to 15
Spark plugs		Champion
Type		N6YCC
Electrode gap	mm	0.80

Electrical system

33, 1.5

1990 to 1992

Battery	V / CC / RC	12 / 255 / 50Ah
Alternator voltage / full load current / engine rpm		14.0 / 55 / 4000
Starter motor current / voltage - cranking	A / V	300 / 9.0
- locked	A / V	400 / 5.0

Running gear

33, 1.5

1990 to 1992

Brakes -		
Front (min. friction material thickness)	mm	7.0 with backing
Rear (min. friction material thickness)	mm	0.50. Discs: 6.5

Tyres		
Saloon	Size	175/70x13: 185/60x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	1.8 / 1.8
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	-4.0±2.0
Camber		+1°14'±30'
Castor		+2°±30'
King pin inclination		—

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0±25']
Camber		0±25'

Torque wrench settings

33, 1.5

1990 to 1992

Cylinder head - stage 1	Nm	29 oiled
- stage 2	Nm	58
Cylinder head - stage 3	Nm	81 to 87
- stage 4	Nm	81 to 87 ¹
Big-end bearings	Nm	43 to 48
Main bearings	Nm	66 to 73 oiled ²
Clutch cover	Nm	15 to 23
Flywheel [driveplate]	Nm	94 to 105 oiled
Front hubs	Nm	427 to 472
Rear hubs	Nm	WSM ³
Wheel nuts / bolts	Nm	88 to 108
Spark plugs	Nm	25 to 34

Capacities

33, 1.5

1990 to 1992

Engine oil & filter	litres	4.0
Gearbox - 4-speed [5-speed]	litres	2.6
Automatic transmission - refill	litres	—
Final drive	litres	WT
Cooling system	litres	7.8
Fuel tank	litres	50

Notes and Illustrations


¹Warm engine, cool, slacken, oil, and retorque bolts in sequence shown to stage 4. No.7: 20 to 24

²Transverse screws: 40 to 49


³Disc brakes: 250 to 300

1: Idle speed


2: CO / Mixture




1490 cm³



1490 cm³



Dellorto DRLA



Weber 40 IDF