

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system100, 2.3E CAT1986 to 1991

Type		NF (100kW) SOHC
Capacity (cm³) / number of cylinders		2309 / 5
Compression ratio / pressure	bar	10.0 / ≥9.0
Oil pressure	bar	[2.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-2-4-5-3
No 1 cylinder position		TBE
Thermostat opening temperature	°C	87
Radiator cap pressure	bar	1.2 to 1.5

Fuel system100, 2.3E CAT1986 to 1991

Idle speed - manual [auto]	rpm	650 to 790 N/A
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Bosch
Type / ref		KE III-Jetronic
Main jet / needle		—
Injection pressure	bar	4.3 to 4.6
Pump pressure	bar	6.1 to 6.5
Octane rating	RON	95[U]

Ignition system100, 2.3E CAT1986 to 1991

Type		FEI
Ignition coil		Bosch
Primary resistance	ohms	0.5 to 1.5
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Bosch
Points gap (air gap)	mm	—
Dwell angle	° (%)	N/A
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	15±1 BTDC @ 650 to 790 N/A
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		NGK
Type		BPR5EKU
Electrode gap	mm	0.70 to 0.90

Electrical system100, 2.3E CAT1986 to 1991

Battery	V / CC / RC	12 / 45Ah
Alternator voltage / full load current / engine rpm		12.5 to 14.5 / _ / 3000
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear100, 2.3E CAT1986 to 1991

Brakes -		
Front (min. friction material thickness)	mm	7.0 with backing
Rear (min. friction material thickness)	mm	7.0 with backing

Tyres		
Saloon	Size	185/70x14: 205/60x15
Estate / Van	Size	185/70x14: 205/60x15
Pressure - front / rear - Saloon	bar	2.2 / 2.0¹
- Estate / Van	bar	2.2 / 2.0¹

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0+5' -10'] 4x4: [+5'+5' -10']
Camber		-30'±30'
Castor		+50'±40'
King pin inclination		—

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[+10'±5'] 4x4: [+10'±10']
Camber		-50'±30'. 4x4: -15'±15'

Torque wrench settings100, 2.3E CAT1986 to 1991

Cylinder head - stage 1	Nm	40 N
- stage 2	Nm	60
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	30 + 90°
Main bearings	Nm	65
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	Without shoulder: 75²
Front hubs	Nm	MT: 200 + 90°
Rear hubs	Nm	200 + 90°
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	20

Capacities100, 2.3E CAT1986 to 1991

Engine oil & filter	litres	4.5
Gearbox - 4-speed [5-speed]	litres	2.6. 4x4: 2.9
Automatic transmission - refill	litres	3.0
Final drive	litres	AT: 1.0³
Cooling system	litres	8.0
Fuel tank	litres	80


Notes and Illustrations

¹4x4 & 205/60x15: 2.1 / 2.1


²With shoulder: 30 + 90°

³4x4 rear: 1.6


1: Idle speed2: CO / Mixture



2309 cm³



2309 cm³



KEIII -Jetronic