


Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive
Technical

DATA
BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

318iS 16V CAT (E30)

1990 to 1991

Type		M42/B18 18 4S1 100kW
Capacity (cm ³) / number of cylinders		1796 / 4
Compression ratio / pressure	bar	10.0 / ≥10.0
Oil pressure	bar	1.3 [4.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		F
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.0±0.1

Fuel system

318iS 16V CAT (E30)

1990 to 1991

Idle speed - manual [auto]	rpm	850±40
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Bosch
Type / ref		M1.7-Motronic
Main jet / needle		—
Injection pressure	bar	2.3 to 2.7
Pump pressure	bar	3.0±0.06
Octane rating	RON	95[U]

Ignition system

318iS 16V CAT (E30)

1990 to 1991

Type		Direct electronic
Ignition coil		Bosch
Primary resistance	ohms	0.8±0.1
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		—
Points gap (air gap)	mm	[0.30 to 0.70]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum		—
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		Bosch/Champion
Type		F8LCR / C9YCC
Electrode gap	mm	0.70 to 0.80

Electrical system

318iS 16V CAT (E30)

1990 to 1991

Battery	V / CC / RC	12 / 50Ah
Alternator voltage / full load current / engine rpm		13.5 to 14.2 / 65 / 3000
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear

318iS 16V CAT (E30)

1990 to 1991

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	195/65x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	1.8 / 1.9
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[+18'±5']
Camber		-40'±30'
Castor		+8°46'±30'
King pin inclination		+14°15'±30' (20° lock)

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[+28'±7']
Camber		-2°20'±30'

Torque wrench settings

318iS 16V CAT (E30)

1990 to 1991

Cylinder head - stage 1	Nm	30 to 32 WSM
- stage 2	Nm	+ 90±3°
Cylinder head - stage 3	Nm	+ 90±3°
- stage 4	Nm	—
Big-end bearings	Nm	23 + 70° N
Main bearings	Nm	22.5±2.5 + 50±3°
Clutch cover	Nm	24. 10.9 hex: 35
Flywheel [driveplate]	Nm	113 to 130 N
Front hubs	Nm	290
Rear hubs	Nm	195 to 210
Wheel nuts / bolts	Nm	100±10
Spark plugs	Nm	30 to 33


Capacities

318iS 16V CAT (E30)

1990 to 1991

Engine oil & filter	litres	4.85
Gearbox - 4-speed [5-speed]	litres	1.1
Automatic transmission - refill	litres	—
Final drive	litres	0.9
Cooling system	litres	6.4
Fuel tank	litres	64

Notes and Illustrations



1796 cm³, 16V