

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive
Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system535i E391996 to 1997

Type	M62 B35 V8 173kW	
Capacity (cm³) / number of cylinders	3498 / 8	
Compression ratio / pressure	bar	10.0 / ≥12.0
Oil pressure	bar	≥0.5 / 4.5
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order	1-5-4-8-6-3-7-2	
No 1 cylinder position	—	
Thermostat opening temperature	°C	85
Radiator cap pressure	bar	—

Fuel system535i E391996 to 1997

Idle speed - manual [auto]	rpm	750±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	0.5±0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	_ Bosch	
Type / ref	DME M5.2-Motronic	
Main jet / needle	—	
Injection pressure	bar	—
Pump pressure	bar	3.5
Octane rating	RON	95[U]

Ignition system535i E391996 to 1997

Type	DME Motronic	
Ignition coil	—	
Primary resistance	ohms	—
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	—	
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static	° Crankshaft @ rpm	—
V = Vacuum NV = No Vacuum	—	
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	—
Maximum vacuum advance	° Crankshaft	—
Spark plugs	Bosch	
Type	F7LDCR	
Electrode gap	mm	0.7

Electrical system535i E391996 to 1997

Battery	V / CC / RC	12 / 90Ah
Alternator voltage / full load current / engine rpm	_ / 140 / _	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear535i E391996 to 1997

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	3.0

Tyres		
Saloon	Size	225/60x15
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	Refer to vehicle
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0°14'±10']
Camber	-0°13'±30'	
Castor	6°36'±30'	
King pin inclination	—	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[0°16'±10']
Camber	-2°10'±20'	

Torque wrench settings535i E391996 to 1997


Cylinder head - stage 1	Nm	30
- stage 2	Nm	+80°
Cylinder head - stage 3	Nm	+80°
- stage 4	Nm	—
Big-end bearings	Nm	5, 20+80°
Main bearings	Nm	WSM
Clutch cover	Nm	24
Flywheel [driveplate]	Nm	105
Front hubs	Nm	—
Rear hubs	Nm	300
Wheel nuts / bolts	Nm	100±10
Spark plugs	Nm	—

Capacities535i E391996 to 1997

Engine oil & filter	litres	7.5
Gearbox - 4-speed [5-speed]	litres	1.2
Automatic transmission - refill	litres	3.3
Final drive	litres	1.0
Cooling system	litres	12.0
Fuel tank	litres	70

Notes and Illustrations

—



3498 cm³ 32V