

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemAX GT CAT1988 to 1990

Type		TU3M (KDZ)
Capacity (cm³) / number of cylinders		1360 / 4
Compression ratio / pressure	bar	8.8 / _
Oil pressure	bar	[4.0]
Oil temperature	°C	90
Valve clearance - inlet	mm	0.20±0.05
Valve clearance - exhaust	mm	0.40±0.05
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	90 to 95
Radiator cap pressure	bar	1.0

Fuel systemAX GT CAT1988 to 1990

Idle speed - manual [auto]	rpm	850±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		Mono-Jetronic SPI
Main jet / needle		_
Injection pressure	bar	1.0
Pump pressure	bar	1.1
Octane rating	RON	95[U]

Ignition systemAX GT CAT1988 to 1990

Type		Electronic - Hall effect
Ignition coil		Ducellier, Marelli BTR 02
Primary resistance	ohms	0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Ducellier/Bosch
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	8±2 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	C055-D043
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	0 @ 1000 to 1400
	° Crankshaft @ rpm	11 to 15 @ 3000
	° Crankshaft @ rpm	21 to 25 @ 5000
Vacuum range check	mbar	130 to 550
Maximum vacuum advance	° Crankshaft	21 to 25
Spark plugs		Eyquem/Champion
Type		FC42LS / C10YCC
Electrode gap	mm	0.80

Electrical systemAX GT CAT1988 to 1990

Battery	V / CC / RC	12 / 250 / _
Alternator voltage / full load current / engine rpm		13.5 / 50 / 3650
Starter motor current / voltage - cranking	A / V	105 / 12
- locked	A / V	220 / _

Running gearAX GT CAT1988 to 1990

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.0

Tyres		
Saloon	Size	165/65x13: 155/65x14:165/60x14
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	1.9 / 2.0¹
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-2.0±1.5
Camber		-30'±30'
Castor		+2°15'±30'
King pin inclination		+12.58°

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.8 to 5.4
Camber		-1°15'±20'

Torque wrench settingsAX GT CAT1988 to 1990


Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 240°
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	40
Main bearings	Nm	20 + 45°
Clutch cover	Nm	13
Flywheel [driveplate]	Nm	65 LkC
Front hubs	Nm	250
Rear hubs	Nm	140
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	25

CapacitiesAX GT CAT1988 to 1990


Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	4.8
Fuel tank	litres	43

Notes and Illustrations

¹165/60x14: 1.9 / 1.9



1360 cm³



1360 cm³