

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemCX 201986 to 1990

Type		J6RA500
Capacity (cm³) / number of cylinders		1995 / 4
Compression ratio / pressure	bar	9.2 / _
Oil pressure	bar	1.4 [4.4]
Oil temperature	°C	90
Valve clearance - inlet	mm	0.10
Valve clearance - exhaust	mm	0.25
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	86
Radiator cap pressure	bar	1.0

Fuel systemCX 201986 to 1990

Idle speed - manual [auto]	rpm	800±50
Fast idle speed - manual [auto]	rpm	1400 to 1500
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤100
CO2 @ idle speed [3000 rpm] - see page VI	%	≥9.0
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Weber
Type / ref		34 DMTR 120 / 100 W 149-50
Main jet / needle		110, 125
Injection pressure	bar	_
Pump pressure	bar	≤0.33
Octane rating	RON	98[E 95 RON]

Ignition systemCX 201986 to 1990

Type		Electronic
Ignition coil		Bosch
Primary resistance	ohms	0.70 to 0.94
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Ducellier
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	10±1 BTDC @ 750
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	R303-D59
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	0 @ 1000 to 1400
	° Crankshaft @ rpm	11 to 15 @ 3000
	° Crankshaft @ rpm	20 to 24 @ 5000
Vacuum range check	mbar	130 to 440
Maximum vacuum advance	° Crankshaft	12 to 16
Spark plugs		Bosch/Champion
Type		H7DC / S9YCC
Electrode gap	mm	0.60 to 0.70

Electrical systemCX 201986 to 1990

Battery	V / CC / RC	12 / 250 / 45, 70Ah
Alternator voltage / full load current / engine rpm		13.5 / _ / 4000
Starter motor current / voltage - cranking	A / V	130 to 160 / _
- locked	A / V	355 to 380 / 6.8 to 7.2

Running gearCX 201986 to 1990

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	185x14: 185/70x14: 195/70x14
Estate / Van	Size	185x14: 195/70x14
Pressure - front / rear - Saloon	bar	2.0 / 2.1 ¹
- Estate / Van	bar	2.0 / 2.2 ²

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0 to 4.0
Camber		0-29'+13'
Castor		-25' to -1°15'
King pin inclination		_

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0 to +4.0
Camber		0+0-24'

Torque wrench settingsCX 201986 to 1990

Cylinder head - stage 1	Nm	50
- stage 2	Nm	80
Cylinder head - stage 3	Nm	93, warm up
- stage 4	Nm	Cool for 2 hours, 93
Big-end bearings	Nm	65
Main bearings	Nm	88 to 98
Clutch cover	Nm	23
Flywheel [driveplate]	Nm	60 to 65 locked
Front hubs	Nm	375
Rear hubs	Nm	400. Estate: 600
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	12


CapacitiesCX 201986 to 1990

Engine oil & filter	litres	5.3
Gearbox - 4-speed [5-speed]	litres	1.8
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	9.6
Fuel tank	litres	68


Notes and Illustrations

¹1986 ►: 2.2 / 2.1
²PAS: 1.9 / 2.1. 195/70x14: 2.4 / 2.0, 1986 ►: 2.5 / 2.3


1: Idle speed 2: CO / Mixture



1995 cm³



1995 cm³



Weber DMTR