

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Uno 70 (1300) 1988 to 1990

Type		149 A7.000 OHC
Capacity (cm ³) / number of cylinders		1301 / 4
Compression ratio / pressure	bar	9.14 / _
Oil pressure	bar	[3.4 to 4.9]
Oil temperature	°C	100
Valve clearance - inlet	mm	0.40±0.05
Valve clearance - exhaust	mm	0.50±0.05
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	80 to 84
Radiator cap pressure	bar	0.98

Fuel system

Uno 70 (1300) 1988 to 1990

Idle speed - manual [auto]	rpm	850±50
Fast idle speed - manual [auto]	rpm	1300
CO @ idle speed [3000 rpm] - see page VI	%	1.0±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Weber
Type / ref		30-32 DMTE 35/150
Main jet / needle		87, 90
Injection pressure	bar	_
Pump pressure	bar	0.18
Octane rating	RON	98[E 95 RON]

Ignition system

Uno 70 (1300) 1988 to 1990

Type		Electronic
Ignition coil		Marelli BAE 506A
Primary resistance	ohms	0.756 to 0.924
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Marelli
Points gap (air gap)	mm	[0.30 to 0.40]
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	10±2 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	0 @ 800 to 1400
	° Crankshaft @ rpm	9 to 13 @ 3000
	° Crankshaft @ rpm	18 to 22 @ 5250
Vacuum range check	mbar	160 to 467
Maximum vacuum advance	° Crankshaft	14 to 16
Spark plugs		Bosch/Champion
Type		WR7DC / RN9YC
Electrode gap	mm	0.70 to 0.80

Electrical system

Uno 70 (1300) 1988 to 1990

Battery	V / CC / RC	12 / 175 / 60
Alternator voltage / full load current / engine rpm		14.0 to 14.4 / _ / 3000
Starter motor current / voltage - cranking	A / V	170 / 9.1
- locked	A / V	320 / 7

Running gear

Uno 70 (1300) 1988 to 1990

Brakes -		
Front (min. friction material thickness)	mm	1.5
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	155/70x13: 165/65x13
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	1.9 / 1.9
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0±1.0
Camber		+25'±30'
Castor		+2°±20'
King pin inclination		_

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	_
Camber		_

Torque wrench settings

Uno 70 (1300) 1988 to 1990

Cylinder head - stage 1	Nm	20
- stage 2	Nm	40
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	51
Main bearings	Nm	80
Clutch cover	Nm	16
Flywheel [driveplate]	Nm	83
Front hubs	Nm	294
Rear hubs	Nm	216
Wheel nuts / bolts	Nm	86
Spark plugs	Nm	25 to 30

Capacities


Uno 70 (1300) 1988 to 1990

Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.4
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	6.2
Fuel tank	litres	42


Notes and Illustrations




1: Idle speed 2: CO / Mixture




1301 cm³



1301 cm³



Weber DMTE



1301 cm³, alternative