

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemMaverick 2.4i1993 to 1996

Type		KA24E. BF. 91kW. 91/441/EEC
Capacity (cm³) / number of cylinders		2389 / 4
Compression ratio / pressure	bar	8.6 / 13.24
Oil pressure	bar	[4.1 to 4.8]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TCE
Thermostat opening temperature	°C	76.5
Radiator cap pressure	bar	0.78 to 0.98

Fuel systemMaverick 2.4i1993 to 1996

Idle speed - manual [auto]	rpm	800±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	—
HC @ idle speed [3000 rpm] - see page VI	ppm	—
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		—
Type / ref		PCM EFI
Main jet / needle		—
Injection pressure	bar	2.26 to 2.94
Pump pressure	bar	—
Octane rating	RON	91[U]

Ignition systemMaverick 2.4i1993 to 1996

Type		Computerized
Ignition coil		—
Primary resistance	ohms	—
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		—
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		—
Ignition timing - basic [static	° Crankshaft @ rpm	10±2 BTDC @ ≤850
V = Vacuum NV = No Vacuum		—
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		_/Champion
Type		RN9YCC
Electrode gap	mm	0.80

Electrical systemMaverick 2.4i1993 to 1996

Battery	V / CC / RC	—
Alternator voltage / full load current / engine rpm		14 / 60, 65, 70/ —
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gearMaverick 2.4i1993 to 1996

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	—
Estate / Van	Size	215/80x15: 235/75x15
Pressure - front / rear - Saloon	bar	—
- Estate / Van	bar	3D: 1.8 / 2.2¹

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+3.0 to 5.0
Camber		0 to +1°
Castor		+1°10' to 2°10'
King pin inclination		+7°36' to 8°36'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	—
Camber		—

Torque wrench settingsMaverick 2.4i1993 to 1996

Cylinder head - stage 1	Nm	29
- stage 2	Nm	78
Cylinder head - stage 3	Nm	- 360° (slacken)
- stage 4	Nm	29 + 83°
Big-end bearings	Nm	15 + 63°
Main bearings	Nm	49
Clutch cover	Nm	26
Flywheel [driveplate]	Nm	147
Front hubs	Nm	WSM
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	123
Spark plugs	Nm	25


CapacitiesMaverick 2.4i1993 to 1996

Engine oil & filter	litres	4.3
Gearbox - 4-speed [5-speed]	litres	3.5. Transfer: 2.3
Automatic transmission - refill	litres	—
Final drive	litres	Rear: 2.8
Cooling system	litres	6.9
Fuel tank	litres	3D: 72. 5D: 80


Notes and Illustrations

¹5D: 1.9 / 2.5

1: Idle speed 2: CO / Mixture



2389 cm³, 12V



PCM EFI