

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemFiesta 14001986 to 1989

Type	FUA / FUB (CVH)	
Capacity (cm³) / number of cylinders	1392 / 4	
Compression ratio / pressure	bar	9.5 / 12.3 to 14.3
Oil pressure	bar	1.0 [2.8]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order	1-3-4-2	
No 1 cylinder position	TBE	
Thermostat opening temperature	°C	85 to 89
Radiator cap pressure	bar	1.0

Fuel systemFiesta 14001986 to 1989

Idle speed - manual [auto]	rpm	800±50
Fast idle speed - manual [auto]	rpm	2700±100
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	Weber	
Type / ref	(2V) DFTM	
Main jet / needle	102, 125	
Injection pressure	bar	—
Pump pressure	bar	0.24 to 0.38
Octane rating	RON	97[RA] ¹

Ignition systemFiesta 14001986 to 1989

Type	Electronic	
Ignition coil	—	
Primary resistance	ohms	0.72 to 0.88
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	Bosch/Lucas	
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	Anticlockwise	
Ignition timing - basic [static	° Crankshaft @ rpm	12 BTDC @ 800 ¹
V = Vacuum NV = No Vacuum	NV	
Total ignition advance	° Crankshaft @ rpm	18 to 30 @ 2000
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	3 to 9 @ 2000
	° Crankshaft @ rpm	6.4 to 12.4 @ 3000
	° Crankshaft @ rpm	10 to 16 @ 4000
Vacuum range check	mbar	0 to 500
Maximum vacuum advance	° Crankshaft	15 to 21
Spark plugs	Motorcraft/Champion	
Type	AGPR22C / RC7YC	
Electrode gap	mm	0.75

Electrical systemFiesta 14001986 to 1989

Battery	V / CC / RC	12 / 150 / 55
Alternator voltage / full load current / engine rpm	13.5 / _ / 3000	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gearFiesta 14001986 to 1989

Brakes -		
Front (min. friction material thickness)	mm	1.5
Rear (min. friction material thickness)	mm	1.0

Tyres		
Saloon	Size	155/70x13
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	1.6 / 1.8
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	-3.0±1.0
Camber	+2°±1°. Sport +1°30'±1°	
Castor	+30'+1°15'-1°. Sport +45'	
King pin inclination	—	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	—
Camber	—	

Torque wrench settingsFiesta 14001986 to 1989

Cylinder head - stage 1	Nm	25 N
- stage 2	Nm	55
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	30 to 36
Main bearings	Nm	90 to 100
Clutch cover	Nm	16 to 20
Flywheel [driveplate]	Nm	82 to 92
Front hubs	Nm	205 to 235
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	100
Spark plugs	Nm	27


CapacitiesFiesta 14001986 to 1989

Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.8 [3.1]
Automatic transmission - refill	litres	—
Final drive	litres	WT
Cooling system	litres	6.3
Fuel tank	litres	40


Notes and Illustrations

¹[E 95 RON]: 8° BTDC @ idle


1: Idle speed 2: CO / Mixture



1392 cm³



1392 cm³



Weber DFTM, ►1989