

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemThema 2000ie1989

Type		154 C.000 DOHC 8V
Capacity (cm³) / number of cylinders		1995 / 4
Compression ratio / pressure	bar	9.5±0.15 / _
Oil pressure	bar	[3.4 to 4.9]
Oil temperature	°C	100
Valve clearance - inlet	mm	0.39±0.04
Valve clearance - exhaust	mm	0.46±0.03
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	81 to 85
Radiator cap pressure	bar	0.98

Fuel systemThema 2000ie1989

Idle speed - manual [auto]	rpm	750±50 [850±50]
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	1.0±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		LE2-Jetronic
Main jet / needle		_
Injection pressure	bar	3.0±0.2
Pump pressure	bar	≤6.0
Octane rating	RON	98[E 95 RON]

Ignition systemThema 2000ie1989

Type		Digiplex
Ignition coil		Marelli BAE 209B
Primary resistance	ohms	0.31 to 0.38
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Marelli
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	20±2 BTDC @ idle
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	10±2 BTDC @ 0 to 1000
	° Crankshaft @ rpm	40±2 BTDC @ 2850 to 5000
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Bosch/Champion
Type		WR6DC / RN7YC
Electrode gap	mm	0.60 to 0.70

Electrical systemThema 2000ie1989

Battery	V / CC / RC	12 / 255 / 85
Alternator voltage / full load current / engine rpm		14.0 to 14.3 / _ / 3500
Starter motor current / voltage - cranking	A / V	270 / 9.2 [360 / 8.5]
- locked	A / V	530 to 570 / 6.6 ¹

Running gearThema 2000ie1989

Brakes -		
Front (min. friction material thickness)	mm	1.5
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	175/70x14: 195/60x14
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.0 / 2.0
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-1.0 to +1.0
Camber		-40' to 0 N/A
Castor		+2°30' to 3°10' N/A
King pin inclination		_

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0 to 4.0
Camber		-40' to 0 N/A

Torque wrench settingsThema 2000ie1989

Cylinder head - stage 1	Nm	40
- stage 2	Nm	+ 90°
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	_
Big-end bearings	Nm	25 + 90°
Main bearings	Nm	20 ²
Clutch cover	Nm	20
Flywheel [driveplate]	Nm	142
Front hubs	Nm	360
Rear hubs	Nm	320
Wheel nuts / bolts	Nm	88
Spark plugs	Nm	37


CapacitiesThema 2000ie1989

Engine oil & filter	litres	5.5
Gearbox - 4-speed [5-speed]	litres	1.8 to 2.1
Automatic transmission - refill	litres	4.4
Final drive	litres	WT
Cooling system	litres	9.0
Fuel tank	litres	70


Notes and Illustrations

- ¹[690 to 730 / 4.8 to 5.2]]
- ²Centre bearing: + 120°. Others: + 80°


1: Idle speed 2: CO / Mixture




1995 cm³, DOHC 8V



1995 cm³, DOHC 8V



LE2-Jetronic



LE2-Jetronic