

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

E280

1995 to 1997

Type	DOHC 24V 142kW	
Capacity (cm³) / number of cylinders	2799 / 6	
Compression ratio / pressure	bar	10.0 / ≥12.0
Oil pressure	bar	0.3 [3.0]
Oil temperature	°C	90
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order	1-5-3-6-2-4	
No 1 cylinder position	F	
Thermostat opening temperature	°C	
Radiator cap pressure	bar	

Fuel system

E280

1995 to 1997

Idle speed - manual [auto]	rpm	—
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	—	
Type / ref		
Main jet / needle	—	
Injection pressure	bar	—
Pump pressure	bar	
Octane rating	RON	95[U]

Ignition system

E280

1995 to 1997

Type	Computerized	
Ignition coil		
Primary resistance	ohms	—
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	Battery
Distributor	—	
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum		
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs	—	
Type		
Electrode gap	mm	

Electrical system

E280

1995 to 1997

Battery	V / CC / RC	12 / 190 / 74Ah
Alternator voltage / full load current / engine rpm	14.0 / 90 / 2490	
Starter motor current / voltage - cranking	A / V	95 / 11.5 (no load)
- locked	A / V	650 to 840 / 3.8

Running gear

E280

1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	3.5
Rear (min. friction material thickness)	mm	2.5

Tyres		
Saloon	Size	215/55x16
Estate / Van	Size	
Pressure - front / rear - Saloon	bar	
- Estate / Van	bar	

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	
Camber		
Castor		
King pin inclination		

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	
Camber		

Torque wrench settings

E280

1995 to 1997

Cylinder head - stage 1	Nm	55. Bolt length ≤167.2mm
- stage 2	Nm	+ 90°
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	—
Big-end bearings	Nm	30 + 90 to 100°
Main bearings	Nm	55 + 90 to 100°
Clutch cover	Nm	—
Flywheel [driveplate]	Nm	30 + 90 to 100°
Front hubs	Nm	WSM
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	30


Capacities

E280

1995 to 1997

Engine oil & filter	litres	
Gearbox - 4-speed [5-speed]	litres	—
Automatic transmission - refill	litres	—
Final drive	litres	—
Cooling system	litres	
Fuel tank	litres	65

Notes and Illustrations



2799 cm³, 24V