

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemBluebird 2.0 (T12/72)1986 to 1990

Type		CA 20S SOHC
Capacity (cm ³) / number of cylinders		1974 / 4
Compression ratio / pressure	bar	9.4 / ≥9.0
Oil pressure	bar	[3.2 to 5.1]
Oil temperature	°C	—
Valve clearance - inlet	mm	0.30 H
Valve clearance - exhaust	mm	0.30 H
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	82
Radiator cap pressure	bar	0.78 to 0.98

Fuel systemBluebird 2.0 (T12/72)1986 to 1990

Idle speed - manual [auto]	rpm	650±100 [750±100]
Fast idle speed - manual [auto]	rpm	2500 to 2800 [2900 to 3200]
CO @ idle speed [3000 rpm] - see page VI	%	1.0±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Hitachi
Type / ref		DCR342-101 [-102, AT]
Main jet / needle		106, 160. T72: 106, 165
Injection pressure	bar	—
Pump pressure	bar	0.20 to 0.27
Octane rating	RON	97[R]

Ignition systemBluebird 2.0 (T12/72)1986 to 1990

Type		Electronic
Ignition coil		Hanshin STC-106
Primary resistance	ohms	1.3 to 1.7
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Hitachi
Points gap (air gap)	mm	[0.30 to 0.50]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	3±1 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	0 @ 1200
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	21 @ 4800
Vacuum range check	mbar	133 to 467
Maximum vacuum advance	° Crankshaft	20
Spark plugs		NGK/Champion
Type		BCPR6ES / RC7YC
Electrode gap	mm	0.80 to 0.90

Electrical systemBluebird 2.0 (T12/72)1986 to 1990

Battery	V / CC / RC	12 / 60Ah
Alternator voltage / full load current / engine rpm		14.1 to 14.7 / _ / 2500
Starter motor current / voltage - cranking	A / V	60 to 100 / 11.5 (no load)
- locked	A / V	—

Running gearBluebird 2.0 (T12/72)1986 to 1990

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	165x14: 185/70x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	1.9 / 1.8
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+1.0 to 3.0
Camber		-25' to +1°5'
Castor		+1°20' to 2°50'
King pin inclination		+13°50' to 15°20' ¹

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	-2.0 to -6.0
Camber		-1°10' to +20'

Torque wrench settingsBluebird 2.0 (T12/72)1986 to 1990

Cylinder head - stage 1	Nm	29
- stage 2	Nm	78, then loosen bolts
Cylinder head - stage 3	Nm	29
- stage 4	Nm	74 to 83
Big-end bearings	Nm	32 to 36
Main bearings	Nm	45 to 54
Clutch cover	Nm	18 to 22
Flywheel [driveplate]	Nm	98 to 108
Front hubs	Nm	235 to 314
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	98 to 118
Spark plugs	Nm	20 to 29


CapacitiesBluebird 2.0 (T12/72)1986 to 1990

Engine oil & filter	litres	3.6
Gearbox - 4-speed [5-speed]	litres	2.7
Automatic transmission - refill	litres	6.8
Final drive	litres	WT
Cooling system	litres	7.3
Fuel tank	litres	60


Notes and Illustrations

¹T72: +14°15' to 15°45'


1: Idle speed 2: CO / Mixture



1974 cm³



1974 cm³



Hitachi