


Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU	HELP
------	------

Engine and cooling systemMicra 1.0i CAT (K11)1993 to 1997

Type		CG10DE DOHC 16V 40kW
Capacity (cm³) / number of cylinders		998 / 4
Compression ratio / pressure	bar	9.5 / ≥11.3
Oil pressure	bar	[2.9]
Oil temperature	°C	—
Valve clearance - inlet	mm	0.33 to 0.41 H
Valve clearance - exhaust	mm	0.36 to 0.44 H
Firing order		1-3-4-2
No 1 cylinder position		TCE
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	0.88

Fuel systemMicra 1.0i CAT (K11)1993 to 1997

Idle speed - manual [auto]	rpm	650±50 [750±50]
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.1 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Nissan
Type / ref		ECCS MPI
Main jet / needle		—
Injection pressure	bar	2.5
Pump pressure	bar	3.0
Octane rating	RON	95[U]

Ignition systemMicra 1.0i CAT (K11)1993 to 1997

Type		Electronic
Ignition coil		—
Primary resistance	ohms	0.8
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Hitachi
Points gap (air gap)	mm	[0.30 to 0.45]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	15±2 BTDC @ 650 [AT: 750]
V = Vacuum NV = No Vacuum		—
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		NGK/Champion
Type		BKR5E-11 / RC9YCC4
Electrode gap	mm	1.00 to 1.10

Electrical systemMicra 1.0i CAT (K11)1993 to 1997

Battery	V / CC / RC	12 / 36Ah
Alternator voltage / full load current / engine rpm		14.1 to 14.7 / 65 / 2500
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gearMicra 1.0i CAT (K11)1993 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	155/70x13
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.2 / 1.9
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	-0.5 to +1.5
Camber		-26’ to 1°4’ N/A
Castor		1°31’ to 3°1’ N/A
King pin inclination		—

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	-0.5 to +1.5 N/A
Camber		-26’ to 1°4’ N/A

Torque wrench settingsMicra 1.0i CAT (K11)1993 to 1997


Cylinder head - stage 1	Nm	39 N
- stage 2	Nm	78
Cylinder head - stage 3	Nm	Slacken, 35
- stage 4	Nm	+60 to 65 ¹
Big-end bearings	Nm	15 +45°
Main bearings	Nm	25 to 30 +60 to 65°
Clutch cover	Nm	22 TO 29
Flywheel [driveplate]	Nm	83 to 93
Front hubs	Nm	148 to 205
Rear hubs	Nm	186 to 255
Wheel nuts / bolts	Nm	98 to 118
Spark plugs	Nm	20 to 29

CapacitiesMicra 1.0i CAT (K11)1993 to 1997


Engine oil & filter	litres	3.0
Gearbox - 4-speed [5-speed]	litres	3.1 to 3.3
Automatic transmission - refill	litres	3.2
Final drive	litres	WT
Cooling system	litres	4.0
Fuel tank	litres	50

Notes and Illustrations

¹Bolts 11 to 15: 6.3 to 8.3



998 cm³, DOHC 16V



998 cm³, DOHC 16V