

PEUGEOT-TALBOT

106, 1.4i CAT

1991 to 1993

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

106, 1.4i CAT

1991 to 1993

Type	TU3F.M/Z (KDY.2) (55kW)	
Capacity (cm³) / number of cylinders	1360 / 4	
Compression ratio / pressure	bar	9.3 / _
Oil pressure	bar	1.5 [3.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20
Valve clearance - exhaust	mm	0.40
Firing order	1-3-4-2	
No 1 cylinder position	FE	
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.4

Fuel system

106, 1.4i CAT

1991 to 1993

Idle speed - manual [auto]	rpm	850±50 N/A
Fast idle speed - manual [auto]	rpm	1300±50 N/A
CO @ idle speed [3000 rpm] - see page VI	%	≤0.4 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	Bosch	
Type / ref	Mono-Jetronic A2.2	
Main jet / needle	_	
Injection pressure	bar	1.0 to 1.2
Pump pressure	bar	2.5
Octane rating	RON	95[U]

Ignition system

106, 1.4i CAT

1991 to 1993

Type	Electronic	
Ignition coil	_	
Primary resistance	ohms	0.7
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	Bosch	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	Anticlockwise	
Ignition timing - basic [static	° Crankshaft @ rpm	8 BTDC @ 900
V = Vacuum NV = No Vacuum	NV	
Total ignition advance	° Crankshaft @ rpm	C060-D049
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	6 to 8 @ 1000
	° Crankshaft @ rpm	18 to 22 @ 3800
	° Crankshaft @ rpm	30 to 34 @ 6200
Vacuum range check	mbar	215 to 640
Maximum vacuum advance	° Crankshaft	20 to 24
Spark plugs	Eyquem/Champion	
Type	RFC52LS / RC9YCC	
Electrode gap	mm	0.80

Electrical system

106, 1.4i CAT

1991 to 1993

Battery	V / CC / RC	12 / 200 or 250 / 33Ah
Alternator voltage / full load current / engine rpm	13.8 to 14.8 / _ / 3000	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear

106, 1.4i CAT

1991 to 1993

Brakes -		
Front (min. friction material thickness)	mm	1.0
Rear (min. friction material thickness)	mm	_

Tyres		
Saloon	Size	155/70x13: 165/65x13
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.0 / 2.0
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+0.5±0.5 PW
Camber	-46'±30'	
Castor	+2°15'±30'	
King pin inclination	+12°49'±40'	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.95±0.9 PW
Camber	-1°34'±30'	

Torque wrench settings

106, 1.4i CAT

1991 to 1993

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 120°
Cylinder head - stage 3	Nm	+ 120°
- stage 4	Nm	_
Big-end bearings	Nm	40
Main bearings	Nm	WSM
Clutch cover	Nm	15
Flywheel [driveplate]	Nm	60 LkC
Front hubs	Nm	250
Rear hubs	Nm	140
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	28


Capacities

106, 1.4i CAT


1991 to 1993

Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	6.0
Fuel tank	litres	45

Notes and Illustrations



1360 cm³, TU3



1360 cm³, TU3