


Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive
Technical
DATA
BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system205, 1.4i CAT1991 to 1994

Type		TU3M/Z (KDY) 58kW
Capacity (cm³) / number of cylinders		1360 / 4
Compression ratio / pressure	bar	9.3 / _
Oil pressure	bar	1.5 [3.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20
Valve clearance - exhaust	mm	0.40
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.0

Fuel system205, 1.4i CAT1991 to 1994

Idle speed - manual [auto]	rpm	850±50 N/A
Fast idle speed - manual [auto]	rpm	1300±50
CO @ idle speed [3000 rpm] - see page VI	%	≤0.4 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		Mono-Jetronic
Main jet / needle		_
Injection pressure	bar	1.0 to 1.2
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system205, 1.4i CAT1991 to 1994

Type		Electronic
Ignition coil		_
Primary resistance	ohms	0.7
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Bosch
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	8±1 BTDC @ 900
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	C060-D049
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	-1 to +1 @ 1400
	° Crankshaft @ rpm	8 to 10 @ 5000
	° Crankshaft @ rpm	11 to 13 @ 6200
Vacuum range check	mbar	200 to 480
Maximum vacuum advance	° Crankshaft	10 to 12
Spark plugs		Eyquem/Champion
Type		FC42LS / C10YCC¹
Electrode gap	mm	0.80

Electrical system205, 1.4i CAT1991 to 1994

Battery	V / CC / RC	12 / 175 / 60
Alternator voltage / full load current / engine rpm		13.8 to 14.8 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear205, 1.4i CAT1991 to 1994

Brakes -		
Front (min. friction material thickness)	mm	1.0
Rear (min. friction material thickness)	mm	_

Tyres		
Saloon	Size	165/70x13
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	1.8 / 2.0
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0±0.5 PW
Camber		0±30'
Castor		+3°±30'
King pin inclination		+9°45'±30'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.7±0.8 PW
Camber		-50'±30'

Torque wrench settings205, 1.4i CAT1991 to 1994


Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 240°
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	40
Main bearings	Nm	WSM
Clutch cover	Nm	15
Flywheel [driveplate]	Nm	65 LkC
Front hubs	Nm	265
Rear hubs	Nm	215
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	28

Capacities205, 1.4i CAT1991 to 1994


Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	5.8
Fuel tank	litres	50

Notes and Illustrations

¹91 ►: RFC52LS / RC9YCC



1360 cm³, TU3



1360 cm³, TU3