

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemPersona 1.81996 to 1997

Type		4G93-0 SOHC 12V
Capacity (cm ³) / number of cylinders		1834 / 4
Compression ratio / pressure	bar	10.0 / 14.0
Oil pressure	bar	—
Oil temperature	°C	—
Valve clearance - inlet	mm	0.09
Valve clearance - exhaust	mm	0.20
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	82
Radiator cap pressure	bar	—

Fuel systemPersona 1.81996 to 1997

Idle speed - manual [auto]	rpm	800±100 N/A
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		—
Type / ref		MPI
Main jet / needle		—
Injection pressure	bar	3.35
Pump pressure	bar	—
Octane rating	RON	95[U]

Ignition systemPersona 1.81996 to 1997

Type		Electronic
Ignition coil		—
Primary resistance	ohms	0.9 to 1.2
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		—
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		—
Ignition timing - basic [static	° Crankshaft @ rpm	5° BTDC @ 800±100
V = Vacuum NV = No Vacuum		—
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		NGK/Nippon Denso
Type		BK5E / K16P-U
Electrode gap	mm	—

Electrical systemPersona 1.81996 to 1997

Battery	V / CC / RC	12 / 53Ah
Alternator voltage / full load current / engine rpm		_ / 75 /
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gearPersona 1.81996 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	185/60x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.0 / 2.0
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+0.0±3.0
Camber		0°00'±30'
Castor		2°15'±30'
King pin inclination		12°49'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+1.0 to 5.0
Camber		-0°40'±30'

Torque wrench settingsPersona 1.81996 to 1997

Cylinder head - stage 1	Nm	75 slacken ¹
- stage 2	Nm	20
Cylinder head - stage 3	Nm	+90°
- stage 4	Nm	+90°
Big-end bearings	Nm	20 +90°
Main bearings	Nm	25 +90° ²
Clutch cover	Nm	15 to 22
Flywheel [driveplate]	Nm	100 (100)
Front hubs	Nm	200 to 260
Rear hubs	Nm	180
Wheel nuts / bolts	Nm	90 to 110
Spark plugs	Nm	—


CapacitiesPersona 1.81996 to 1997

Engine oil & filter	litres	3.8
Gearbox - 4-speed [5-speed]	litres	1.8
Automatic transmission - refill	litres	6.1
Final drive	litres	WT
Cooling system	litres	5.0
Fuel tank	litres	50

Notes and Illustrations

¹Bolt shank length ≤96.4 mm

²Bolt shank length ≤71.1 mm



1834 cm³ 12V