

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994

Type		J7R-G7-54 (12 valve) 104kW ¹
Capacity (cm ³) / number of cylinders		1995 / 4
Compression ratio / pressure	bar	9.3 / _
Oil pressure	bar	1.3 [3.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.15 to 0.20
Valve clearance - exhaust	mm	0.20 to 0.25
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	89 to 101
Radiator cap pressure	bar	1.2

Fuel system

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994

Idle speed - manual [auto]	rpm	850±75. CAT: 800±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	≥14.5
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Renix
Type / ref		Fenix 3B MPI
Main jet / needle		_
Injection pressure	bar	2.5±0.2
Pump pressure	bar	3.0±0.2
Octane rating	RON	98[E 95 RON] ²

Ignition system

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994

Type		Computerized
Ignition coil		Renix
Primary resistance	ohms	0.4 to 0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Renix
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control
V = Vacuum NV = No Vacuum		_
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Eyquem/Champion
Type		FC62LS3 / C7YCC
Electrode gap	mm	1.20 N/A

Electrical system

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994

Battery	V / CC / RC	12 / 210 / 65
Alternator voltage / full load current / engine rpm		13.5 to 14.8 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	6.0 with backing

Tyres		
Saloon	Size	185/65x14: 185/55x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.3 / 2.3
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-2.0±1.0
Camber		-35'±30'
Castor		+2°±30'
King pin inclination		+13°5'±30'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+2.0 to 5.0
Camber		-20'±10'

Torque wrench settings

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 80° + 80°
Cylinder head - stage 3	Nm	Run for 15 mins.
- stage 4	Nm	Cool for 3 hours, then + 20°
Big-end bearings	Nm	45 to 50
Main bearings	Nm	88 to 98
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	60 [65 to 70]
Front hubs	Nm	250
Rear hubs	Nm	160. 4x4: 210
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	28±2

Capacities

21, 2.0 TXi & CAT (X48Q/Y/R)

1989 to 1994


Engine oil & filter	litres	5.5
Gearbox - 4-speed [5-speed]	litres	2.2. 4x4: 3.35
Automatic transmission - refill	litres	_
Final drive	litres	4x4 rear: 1.3
Cooling system	litres	7.1
Fuel tank	litres	66. 4x4: 62

Notes and Illustrations


¹CAT: J7R-7-40

²CAT: 95 [U]

1: Idle speed 2: CO / Mixture



1995 cm³, 12V



Renix R electronic