

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

5, Extra 1.4 (B/C/F402)

1985 to 1991

Type		C1J-A7-68 or C1J-E7-68
Capacity (cm³) / number of cylinders		1397 / 4
Compression ratio / pressure	bar	9.2 / _
Oil pressure	bar	0.7 [3.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.15
Valve clearance - exhaust	mm	0.20
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	83
Radiator cap pressure	bar	0.9

Fuel system

5, Extra 1.4 (B/C/F402)

1985 to 1991

Idle speed - manual [auto]	rpm	625±25
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	1.0±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Solex/Zenith
Type / ref		S: 32 BIS 849. Z: 32 IF2 ...11
Main jet / needle		S: 112.5. Z: 124
Injection pressure	bar	_
Pump pressure	bar	0.17 to 0.33
Octane rating	RON	98[E 95 RON]

Ignition system

5, Extra 1.4 (B/C/F402)

1985 to 1991

Type		AEI
Ignition coil		Renix
Primary resistance	ohms	0.4 to 0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Renix
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	10±1 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	RE204
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	9 to 11 @ 650
	° Crankshaft @ rpm	13 to 15 @ 1550
	° Crankshaft @ rpm	26 to 29 @ 4050
Vacuum range check	mbar	300 @ 4550 rpm
Maximum vacuum advance	° Crankshaft	≥10
Spark plugs		Bosch/Champion
Type		W8DC / N281YC
Electrode gap	mm	0.75 to 0.85

Electrical system

5, Extra 1.4 (B/C/F402)

1985 to 1991

Battery	V / CC / RC	12 / 175 / 60
Alternator voltage / full load current / engine rpm		13.5 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	340 to 460 / _

Running gear

5, Extra 1.4 (B/C/F402)

1985 to 1991

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	2.5 with backing

Tyres		
Saloon	Size	145/70x13: 155/70x13
Estate / Van	Size	145x13: 155x13
Pressure - front / rear - Saloon	bar	2.0 / 2.2
- Estate / Van	bar	2.1 / 2.5

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-1.0±1.0
Camber		+15'±30' [Extra: +30'±30']
Castor		+2°±30'
King pin inclination		+12°40'±30' [Extra: +12°10']

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	0 to +3.0 ¹
Camber		-50'±30'

Torque wrench settings

5, Extra 1.4 (B/C/F402)

1985 to 1991

Cylinder head - stage 1	Nm	55 to 65
- stage 2	Nm	_
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	45
Main bearings	Nm	55 to 65
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	50
Front hubs	Nm	250
Rear hubs	Nm	160
Wheel nuts / bolts	Nm	80
Spark plugs	Nm	_

Capacities

5, Extra 1.4 (B/C/F402)

1985 to 1991


Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	Steel: [3.4] ²
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	5.5
Fuel tank	litres	43

Notes and Illustrations


¹Extra: +2.0 to 5.0

²Plastic plug: [2.9]


1: Idle speed 2: CO / Mixture




1397 cm³




1397 cm³



Zenith 32 IF2



Solex 32 BIS



Solex 32 BIS, alternative