

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemMontego 1.61984 to 1988

Type	16H (S Series)	
Capacity (cm ³) / number of cylinders	1598 / 4	
Compression ratio / pressure	bar	9.6 / _
Oil pressure	bar	0.7 [3.8]
Oil temperature	°C	_
Valve clearance - inlet	mm	0.35 to 0.38 ¹
Valve clearance - exhaust	mm	0.43 to 0.46 ¹
Firing order	1-3-4-2	
No 1 cylinder position	TBE	
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.04

Fuel systemMontego 1.61984 to 1988

Idle speed - manual [auto]	rpm	750±50 [825±50]
Fast idle speed - manual [auto]	rpm	1200±50 [1350±50]
CO @ idle speed [3000 rpm] - see page VI	%	2.0 to 3.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	SU	
Type / ref	HIF44E	
Main jet / needle	0.100 / BFM	
Injection pressure	bar	_
Pump pressure	bar	0.3
Octane rating	RON	97[L]

Ignition systemMontego 1.61984 to 1988

Type	Computerized	
Ignition coil	Unipart GCL 139, 143	
Primary resistance	ohms	0.71 to 0.81
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	Lucas	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	Anticlockwise	
Ignition timing - basic [static	° Crankshaft @ rpm	10 to 16 BTDC @ 1000
V = Vacuum NV = No Vacuum	NV	
Total ignition advance	° Crankshaft @ rpm	23 to 27 @ 1000
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	Unipart/Champion	
Type	GSP665, 4562 / C9YC	
Electrode gap	mm	1.00

Electrical systemMontego 1.61984 to 1988

Battery	V / CC / RC	12 / 360 / 70
Alternator voltage / full load current / engine rpm	14.0 / _ / 3000	
Starter motor current / voltage - cranking	A / V	55 to 65 / 12
- locked	A / V	360 to 425 / 7

Running gearMontego 1.61984 to 1988

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	165x13: 180/65x365: 185/65x14
Estate / Van	Size	165x13: 180/65x365: 185/65x14
Pressure - front / rear - Saloon	bar	1.8 / 2.0
- Estate / Van	bar	2.0 / 2.2

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[0±8']
Camber	A: -15'±21'. B: +30'±21' ²	
Castor	+37'±30'	
King pin inclination	A: +12°30'±30'. B: +12°33' ²	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+20' to 40']
Camber	0 to -1°	

Torque wrench settingsMontego 1.61984 to 1988

Cylinder head - stage 1	Nm	40 Lightly oiled
- stage 2	Nm	80
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	_
Big-end bearings	Nm	45
Main bearings	Nm	90
Clutch cover	Nm	15
Flywheel [driveplate]	Nm	75
Front hubs	Nm	203
Rear hubs	Nm	68
Wheel nuts / bolts	Nm	72
Spark plugs	Nm	18


CapacitiesMontego 1.61984 to 1988

Engine oil & filter	litres	3.8
Gearbox - 4-speed [5-speed]	litres	1.5 [2.0]
Automatic transmission - refill	litres	2.3
Final drive	litres	AT: 0.75
Cooling system	litres	8.5
Fuel tank	litres	50


Notes and Illustrations

- ¹Adjust only if less than 0.30
²A = early negative offset steering geometry, B = later positive


1: Idle speed 2: CO / Mixture



1598 cm³



1598 cm³



SU HIF44E