

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system214, 414 SOHC 8V CAT1992 to 1996

Type		1.4 K8 SOHC 8V 56kW
Capacity (cm³) / number of cylinders		1397 / 4
Compression ratio / pressure	bar	9.75 / _
Oil pressure	bar	1.0 [≤7.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	80 to 84
Radiator cap pressure	bar	0.9 to 1.0

Fuel system214, 414 SOHC 8V CAT1992 to 1996

Idle speed - manual [auto]	rpm	875±50 ECU Controlled
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤1.0
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Rover.
Type / ref		Indirect SPI with MEMS
Main jet / needle		_
Injection pressure	bar	1.1
Pump pressure	bar	≤4.1
Octane rating	RON	95[U]

Ignition system214, 414 SOHC 8V CAT1992 to 1996

Type		MEMS
Ignition coil		NEC 10002, 10003
Primary resistance	ohms	0.71 to 0.81
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		_
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	14±5 BTDC @ 875±50
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Unipart/Champion
Type		GSP6662 / RC9YCC
Electrode gap	mm	0.85±0.05

Electrical system214, 414 SOHC 8V CAT1992 to 1996

Battery	V / CC / RC	12 / 360 / 60, 12 / 405 / 70
Alternator voltage / full load current / engine rpm		_ / 65 / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear214, 414 SOHC 8V CAT1992 to 1996

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	2.0. Discs: 3.0

Tyres		
Saloon	Size	155x13: 175/65x14
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.1 / 2.1
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[-10'±15'] U/L
Camber		-20'±10' U/L
Castor		+1°59'±30' U/L
King pin inclination		+12° U/L

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+11'±7.5'] PW U/L
Camber		-50' to +50' U/L

Torque wrench settings214, 414 SOHC 8V CAT1992 to 1996

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 180°
Cylinder head - stage 3	Nm	+ 180°
- stage 4	Nm	_
Big-end bearings	Nm	20 + 45°
Main bearings	Nm	WSM
Clutch cover	Nm	18
Flywheel [driveplate]	Nm	85 N
Front hubs	Nm	185
Rear hubs	Nm	185
Wheel nuts / bolts	Nm	100
Spark plugs	Nm	25


Capacities214, 414 SOHC 8V CAT1992 to 1996

Engine oil & filter	litres	4.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	5.0
Fuel tank	litres	55


Notes and Illustrations



1: Idle speed2: CO / Mixture



1397 cm³, 8V



1397 cm³, 8V