

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling systemMetro 1.0 LC1986 to 1990

Type		99HB / HD / HE ¹
Capacity (cm ³) / number of cylinders		998 / 4
Compression ratio / pressure	bar	8.3 / _
Oil pressure	bar	1.0 [4.1]
Oil temperature	°C	_
Valve clearance - inlet	mm	0.27 to 0.33
Valve clearance - exhaust	mm	0.27 to 0.33
Firing order		1-3-4-2
No 1 cylinder position		TCE
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.04

Fuel systemMetro 1.0 LC1986 to 1990

Idle speed - manual [auto]	rpm	830±100 (89 ►: 830±50)
Fast idle speed - manual [auto]	rpm	1250 to 1350 (99HE: 1100±50)
CO @ idle speed [3000 rpm] - see page VI	%	1.5 to 3.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		SU
Type / ref		HIF38
Main jet / needle		0.090 / ADU
Injection pressure	bar	_
Pump pressure	bar	0.4
Octane rating	RON	91[L] ¹

Ignition systemMetro 1.0 LC1986 to 1990

Type		Contact breaker - CIS
Ignition coil		GCL 144
Primary resistance	ohms	1.3 to 1.5
Ballast resistor	ohms	1.3 to 1.5
Voltage - Tmnl 15(+) to earth	V	6.0 to 8.0
Distributor		Lucas/Ducellier
Points gap (air gap)	mm	0.38±0.03
Dwell angle	° (%)	L: 54±5. D: 57±2.5
Condenser capacity	µF	0.18 to 0.25
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	14 to 16 BTDC @ 1500
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	4 to 8 @ 1000
	° Crankshaft @ rpm	14 to 18 @ 2800
	° Crankshaft @ rpm	20 to 24 @ 4800
Vacuum range check	mbar	33 to 372
Maximum vacuum advance	° Crankshaft	12 to 16
Spark plugs		Unipart/Champion
Type		GSP4382 / N12YC
Electrode gap	mm	0.65

Electrical systemMetro 1.0 LC1986 to 1990

Battery	V / CC / RC	12 / _
Alternator voltage / full load current / engine rpm		14.0 / _ / 3000
Starter motor current / voltage - cranking	A / V	75 / 12 (no load)
- locked	A / V	380 / 7.0

Running gearMetro 1.0 LC1986 to 1990

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	1.6

Tyres		
Saloon	Size	160/65x315
Estate / Van	Size	160/65x315: 160/60x315
Pressure - front / rear - Saloon	bar	2.0 / 1.8
- Estate / Van	bar	2.0 / 2.2

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[0 to -25']
Camber		0±30'
Castor		+2°6'±2°
King pin inclination		+10°38'

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+10' to +50']
Camber		-1°±30'

Torque wrench settingsMetro 1.0 LC1986 to 1990

Cylinder head - stage 1	Nm	38 lightly oiled
- stage 2	Nm	75
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	Bolts: 50. Nuts: 45
Main bearings	Nm	85
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	Centre bolt: 152
Front hubs	Nm	2 hole shaft: 271 ²
Rear hubs	Nm	88
Wheel nuts / bolts	Nm	57
Spark plugs	Nm	25

CapacitiesMetro 1.0 LC1986 to 1990


Engine oil & filter	litres	4.8
Gearbox - 4-speed [5-speed]	litres	With engine
Automatic transmission - refill	litres	_
Final drive	litres	With engine
Cooling system	litres	4.8
Fuel tank	litres	33

Notes and Illustrations


¹Engine codes: 99HB96P/98P/97P/99P/99HD32P/33P/34P/35P/99H E38/39. 99HE38 / 39 89 ►: [E 95 RON]

²1 hole shaft: 262


1: Idle speed 2: CO / Mixture



998 cm³



998 cm³



SU HIF