

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Favorit & Foreman 135

1991 to 1993

Type		135 OHV 43kW 15.04
Capacity (cm ³) / number of cylinders		1289 / 4
Compression ratio / pressure	bar	8.8 / _
Oil pressure	bar	[4.1 to 5.5]
Oil temperature	°C	70
Valve clearance - inlet	mm	0.20. Alloy: 0.25
- exhaust	mm	0.20
Firing order		1-3-4-2
No 1 cylinder position		TCE
Thermostat opening temperature	°C	88 to 103
Radiator cap pressure	bar	1.0

Fuel system

Favorit & Foreman 135

1991 to 1993

Idle speed - manual [auto]	rpm	780 to 830
Fast idle speed - manual [auto]	rpm	2300
CO @ idle speed [3000 rpm] - see page VI	%	0.5 to 1.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤500
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Jikov
Type / ref		28-30 LEKR
Main jet / needle		92.5, 120
Injection pressure	bar	_
Pump pressure	bar	0.30
Octane rating	RON	91[E 91 RON]

Ignition system

Favorit & Foreman 135

1991 to 1993

Type		Electronic
Ignition coil		Pal-Magneton 443 212 215 820
Primary resistance	ohms	0.6
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Pal-Magnetron
Points gap (air gap)	mm	[0.30]
Dwell angle	° (%)	5 to 40
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	2±2 BTDC @ 835±50
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	0 to 4 @ 800 to 1200
	° Crankshaft @ rpm	7 to 15 @ 2000
	° Crankshaft @ rpm	26 to 34 @ 4200
Vacuum range check	mbar	150 to 350
Maximum vacuum advance	° Crankshaft	18 to 22
Spark plugs		Pal
Type		D17YC, G17YC
Electrode gap	mm	0.60 to 0.90

Electrical system

Favorit & Foreman 135

1991 to 1993

Battery	V / CC / RC	12 / 40Ah
Alternator voltage / full load current / engine rpm		14.0 / 55 / 3000
Starter motor current / voltage - cranking	A / V	150 to 210 / 9.5
- locked	A / V	340 / 8.0

Running gear

Favorit & Foreman 135

1991 to 1993

Brakes -		
Front (min. friction material thickness)	mm	8.0
Rear (min. friction material thickness)	mm	1.0

Tyres		
Saloon	Size	165/70x13
Estate / Van	Size	165/70x13
Pressure - front / rear - Saloon	bar	1.9 / 1.8
- Estate / Van	bar	1.9 / 1.8

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0±1.0
Camber		+20'±30'
Castor		+1°30'±45'
King pin inclination		_

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.2±1.4
Camber		-1°24'±30'

Torque wrench settings

Favorit & Foreman 135

1991 to 1993

Cylinder head - stage 1	Nm	BOLTS: 17 to 20
- stage 2	Nm	+ 90°
- stage 3	Nm	+ 90°
- stage 4	Nm	NUTS: 20 to 26
Big-end bearings	Nm	36 to 40
Main bearings	Nm	60mm pin:50 to 55 ¹
Clutch cover	Nm	23 to 28
Flywheel [driveplate]	Nm	55 to 65
Front hubs	Nm	240 to 270
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	60 to 70
Spark plugs	Nm	20 to 30 ²

Capacities

Favorit & Foreman 135


1991 to 1993

Engine oil & filter	litres	4.0 [+ cooler 0.6]
Gearbox - 4-speed [5-speed]	litres	2.4
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	6.0
Fuel tank	litres	47


Notes and Illustrations

- ¹M11: 65 to 75
- ²Flat seat only. Taper seat: 10 to 14


1: Idle speed 2: CO / Mixture



1289 cm³



1289 cm³



Jikov LEKR