



Automotive Technical

DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Celica 1.8i

1995 to 1997

Type	7A-FE DOHC 16V 85kW	
Capacity (cm ³) / number of cylinders	1762 / 4	
Compression ratio / pressure	bar	9.5 / 13.2
Oil pressure	bar	[2.5 to 5.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.15 to 0.25
- exhaust	mm	0.25 to 0.35
Firing order	1-3-4-2	
No 1 cylinder position	TBE	
Thermostat opening temperature	°C	80 to 84
Radiator cap pressure	bar	0.80 to 1.10

Fuel system

Celica 1.8i

1995 to 1997

Idle speed - manual [auto]	rpm	700±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤100
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	_Toyota	
Type / ref	MPI (D Jetronic)	
Main jet / needle	—	
Injection pressure	bar	2.7 to 3.1
Pump pressure	bar	—
Octane rating	RON	95[U]

Ignition system

Celica 1.8i

1995 to 1997

Type	Computerized	
Ignition coil	—	
Primary resistance	ohms	0.45 to 0.65
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	—	
Points gap (air gap)	mm	[0.20 to 0.50]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static	° Crankshaft @ rpm	10 BTDC @ 700±50
V = Vacuum NV = No Vacuum	—	
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs	NGK	
Type	BKR6EP13	
Electrode gap	mm	1.30

Electrical system

Celica 1.8i

1995 to 1997

Battery	V / CC / RC	12 / 60Ah
Alternator voltage / full load current / engine rpm	13.5 to 15.1 / 70 / _	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear

Celica 1.8i

1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	1.0
Rear (min. friction material thickness)	mm	1.0

Tyres		
Saloon	Size	195/65x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	Refer to vehicle
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	0.0±1.0
Camber	-10'±45'	
Castor	1°±45'	
King pin inclination	14°10'±45'	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	5.0±1.0
Camber	-45'±45'	

Torque wrench settings

Celica 1.8i

1995 to 1997

Cylinder head - stage 1	Nm	29
- stage 2	Nm	+ 90°
- stage 3	Nm	+ 90°
- stage 4	Nm	—
Big-end bearings	Nm	29 + 90°
Main bearings	Nm	60
Clutch cover	Nm	19
Flywheel [driveplate]	Nm	78
Front hubs	Nm	186
Rear hubs	Nm	123
Wheel nuts / bolts	Nm	103
Spark plugs	Nm	18

Capacities


Celica 1.8i

1995 to 1997


Engine oil & filter	litres	3.9
Gearbox - 4-speed [5-speed]	litres	2.6
Automatic transmission - refill	litres	—
Final drive	litres	WT
Cooling system	litres	6.5
Fuel tank	litres	60

Notes and Illustrations





1762 cm³, 16V



1762 cm³, 16V