

VAUXHALL/OPEL

Cavalier/Ascona 2.0i

1986 to 1988

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Cavalier/Ascona 2.0i

1986 to 1988

Type		20NE SOHC. 85kW. 15.04
Capacity (cm ³) / number of cylinders		1998 / 4
Compression ratio / pressure	bar	9.2 / _
Oil pressure	bar	1.5
Oil temperature	°C	60
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	92
Radiator cap pressure	bar	1.30 to 1.35

Fuel system

Cavalier/Ascona 2.0i

1986 to 1988

Idle speed - manual [auto]	rpm	720 to 880
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤1.0
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		Motronic ML4.1
Main jet / needle		_
Injection pressure	bar	2.5±0.2
Pump pressure	bar	2.5±0.2
Octane rating	RON	98[E 95 RON] ¹

Ignition system

Cavalier/Ascona 2.0i

1986 to 1988

Type		DME Motronic
Ignition coil		Bosch 90 240 252
Primary resistance	ohms	0.6 to 0.9
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Bosch
Points gap (air gap)	mm	_
Dwell angle	° (%)	Electronic control
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	10±2 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		AC/Champion
Type		CR42XLS / RN7YC
Electrode gap	mm	0.70 to 0.80

Electrical system

Cavalier/Ascona 2.0i

1986 to 1988

Battery	V / CC / RC	12 / 210 / 65
Alternator voltage / full load current / engine rpm		13.7 to 14.5 / _ / 2000
Starter motor current / voltage - cranking	A / V	400 to 500 / 7.0 to 8.2 (AC)
- locked	A / V	475 to 600 / 12 (Bosch)

Running gear

Cavalier/Ascona 2.0i

1986 to 1988

Brakes -		
Front (min. friction material thickness)	mm	7.0 with backing
Rear (min. friction material thickness)	mm	0.5 above rivets

Tyres		
Saloon	Size	195/60x14
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.1 / 1.9
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0 to 3.0
Camber		-1°15' to +15'
Castor		0 to +2°
King pin inclination		_

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+2.0 to 6.0
Camber		0 to -1°

Torque wrench settings

Cavalier/Ascona 2.0i

1986 to 1988

Cylinder head - stage 1	Nm	25 N
- stage 2	Nm	+90°
Cylinder head - stage 3	Nm	+90°
- stage 4	Nm	+90°
Big-end bearings	Nm	35 + 45°
Main bearings	Nm	60 + 40° to 50°
Clutch cover	Nm	15
Flywheel [driveplate]	Nm	65 + 30° to 45° [65]
Front hubs	Nm	100 ²
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	25

Capacities

Cavalier/Ascona 2.0i

1986 to 1988


Engine oil & filter	litres	4.0
Gearbox - 4-speed [5-speed]	litres	2.1
Automatic transmission - refill	litres	7.0
Final drive	litres	WT
Cooling system	litres	6.9
Fuel tank	litres	61

Notes and Illustrations


¹Octane rating plug = 95 RON

²Slacken, then 20 + 90°


1: Idle speed 2: CO / Mixture



1998 cm³, 8V



ML4.1-Motronic



ML4.1-Motronic