

# 0 GENERAL



VEHICLE IDENTIFICATION .....	0-2
MAJOR SPECIFICATIONS .....	0-3

## VEHICLE IDENTIFICATION

## MODELS

Model code		Engine model	Transmission model	Fuel supply system
K62T	JERDEL6	4G63-SOHC (1,997 mℓ)	R4AW2 (2WD-4A/T)	MPI
	ENDEL6		R5M21 (2WD-5M/T)	
K64T	YNDL6	4D56 (2,477 mℓ)		Fuel injection
	ZNDL6			
	ENDL6			
	ENDR6			
	CENDL6			
	JENDL6			
K75T	CENDEL6	4G64-SOHC (2,351 mℓ)	V5M21 (4WD-5M/T)	MPI
K74T	YNDFL6	4D56 with intercooler turbocharger (2,477 mℓ)	V5MT1 (4WD-5M/T)	Fuel injection
	ZNDFL6			
	ENDFR6			
	JERDFL6		V4AW2 (4WD-4A/T)	
	GJENXFL6		V5MT1 (4WD-5M/T)	
	CENDFL6			
	JENDFL6			
	JENHFL6			

**MAJOR SPECIFICATIONS****<2WD Single cab>**

Items	K62T	K64T	K64T	K64T
	ENDEL6	ENDL6	YNDL6	ENDR6
Dimensions mm				
Overall length	4,935	4,935	4,775	4,935
Overall width	1,695	1,695	1,695	1,695
Overall height (unladen)	1,585	1,585	1,585	1,585
Wheelbase	2,950	2,950	2,950	2,950
Track-front	1,450	1,450	1,450	1,450
Track-rear	1,435	1,435	1,435	1,435
Body overhang				
Front	775	775	775	775
Rear	1,210	1,210	–	1,210
Ground clearance (unladen)	190	190	190	190
Wheel alignment	0 – 7 0° – 0°19' 0°10' – 1°10' (Difference between right and left within 30') 1°45' – 3°45' (Difference between right and left within 30') 15°00' 0 0°			
Front wheel alignment				
Toe-in (at the centre of tyre tread) mm				
Toe angle (per wheel)				
Camber				
Caster				
Kingpin inclination angle				
Rear wheel alignment				
Toe-in mm				
Camber				
Wheels and tyres	185R14C-8PR 14 × 6JJ 33			
Tyre size				
Wheel size				
Offset mm				

**<2WD Club cab, Double cab>**

Items	K64T	K62T	K64T	K64T
	CENDL6	JERDEL6	JENDL6	ZNDL6
Dimensions mm				
Overall length	5,050	4,935	4,935	4,775
Overall width	1,695	1,695	1,695	1,695
Overall height (unladen)	1,605	1,610	1,610	1,625
Wheelbase	2,950	2,950	2,950	2,950
Track-front	1,450	1,450	1,450	1,450
Track-rear	1,435	1,435	1,435	1,435
Body overhang				
Front	775	775	775	775
Rear	1,210	1,210	–	1,210
Ground clearance (unladen)	190	190	190	190

Items	K64T	K62T	K64T	K64T
	CENDL6	JERDEL6	JENDL6	ZNDL6
Wheel alignment Front wheel alignment Toe-in (at the centre of tyre tread) mm Toe angle (per wheel) Camber Caster Kingpin inclination angle Rear wheel alignment Toe-in mm Camber	0 – 7 0° – 0°19' 0°10' – 1°10' (Difference between right and left within 30') 1°45' – 3°45' (Difference between right and left within 30') 15°00' 0 0°			
Wheels and tyres Tyre size Wheel size Offset mm	185R14C-8PR 14 × 6JJ 33			

## &lt;4WD Single cab, Club cab&gt;

Items	K74T	K74T	K75T	K74T
	YNDFL6	ENDFR6	CENDEL6	CENDFL6
Dimensions mm Overall length Overall width Overall height (unladen) Wheelbase Track-front Track-rear Body overhang Front Rear Ground clearance (unladen)	4,810 1,695 1,755 2,960 1,420 1,435 765 – 215	4,935 1,695 1,755 2,960 1,420 1,435 765 1,210 215	5,050 1,695 1,775 2,960 1,420 1,435 765 1,325 215	5,050 1,695 1,775 2,960 1,420 1,435 765 1,325 215
Wheel alignment Front wheel alignment Toe-in (at the centre of tyre tread) mm Toe angle (per wheel) Camber Caster Kingpin inclination angle Rear wheel alignment Toe-in mm Camber	0 – 7 0° – 0°16' 0°10' – 1°10' (Difference between right and left within 30') 1°15' – 3°15' (Difference between right and left within 30') 14°50' 0 0°			
Wheels and tyres Tyre size Wheel size Offset mm	205R16 16 × 6JJ 33			

## &lt;4WD Double cab&gt;

Items	K74T	K74T	K74T	K74T	K74T
	JENDFL6	ZNDFL6	JERDFL6	JENHFL6	GJENXFL6
Dimensions mm					
Overall length	4,935	4,810	4,935	4,935	4,935
Overall width	1,695	1,695	1,695	1,695	1,775
Overall height (unladen)	1,780	1,795	1,780	1,780	1,800
Wheelbase	2,960	2,960	2,960	2,960	2,960
Track-front	1,420	1,420	1,420	1,420	1,465
Track-rear	1,435	1,435	1,435	1,435	1,480
Body overhang					
Front	765	765	765	765	765
Rear	1,210	1,210	1,210	1,210	1,210
Ground clearance (unladen)	215	215	215	215	235
Wheel alignment	<div>0 – 7</div> <div>0° – 0°16'; 0° – 0°15'*</div> <div>0°10' – 1°10' (Difference between right and left within 30')</div> <div>1°15' – 3°15' (Difference between right and left within 30')</div> <div>14°50'</div> <div>0</div> <div>0°</div>				
Front wheel alignment					
Toe-in (at the centre of tyre tread) mm					
Toe angle (per wheel)					
Camber					
Caster					
Kingpin inclination angle					
Rear wheel alignment					
Toe-in mm					
Camber					
Wheels and tyres					
Tyre size	205R16				31 × 10.5 R15
Wheel size	16 × 6JJ				7J-15
Offset mm	33				10 ± 1

## NOTE

\* Vehicles with 31 × 10.5 R15 tyres.