
GROUP 0

GENERAL

CONTENTS

VEHICLE IDENTIFICATION	0-2	MAJOR SPECIFICATIONS	0-3
------------------------------	-----	----------------------------	-----

VEHICLE IDENTIFICATION

M4000001001397

MODELS

Model code		Engine model	Price class	Transmission model	Fuel supply system
CU2W	XNMML6	4G63-DOHC-Non-Turbo (1,997 mL)	Invite	F5M42 <2WD, 5M/T>	MPI
	XNMML6			W5M42 <4WD, 5M/T>	
	XNHMZL6		Intense		
	XNXFZL6	4G63-DOHC-Turbo (1,997 mL)	Turbo	W5M51 <4WD, 5M/T>	
CU5W	XNHYZL6	4G69-SOHC MIVEC (2,378 mL)	Intense	W5M42 <4WD, 5M/T>	
	XRHYZL6			W4A4B <4WD, 4A/T with sport mode>	

MAJOR SPECIFICATIONS

M4000003001100

Items		CU2W					
		XNMML6	XNMMZL6	XNHMZL6	XNXFZL6		
Vehicle dimension mm	Overall length	4,545					
	Overall width	1,750		1,780			
	Overall height (unladen)	1,620/1,670 ^{*1}					
	Wheelbase	2,625					
	Track	Front	1,495	1,510			
		Rear	1,505	1,520			
	Front overhang	945					
	Rear overhang	975					
Ground clearance (unladen)		195		170			
Vehicle wheel alignment	Front	Toe-in (at the centre of tyre tread) mm	1 ± 2				
		Toe angle (per wheel)	0°03' ± 05'				
		Toe-out angle on turns (inner wheel outer wheel at 20°)	22°00' ± 1° 30'				
		Camber	- 0°10' ± 30' ^{*2}				
		Caster	3°15' ± 30' ^{*2}				
		Kingpin inclination angle	12°25' ± 1°30'				
	Steering angle	Side slip (per 1m) mm	0 ± 3				
		Inner wheels	34°50' ± 1°30'				
		Outer wheels (reference)	29°20'				
		Rear	Toe-in (at the centre of tyre tread) mm	3 ± 2			
		Toe angle (per wheel)	0°08' ± 05'				
		Camber	- 0°40' ± 30' ^{*2}				
Wheels and tyres		Tyre size	215/60R16 95H	215/55R17 94V , 215/60R16 95H ^{*3}	215/55R17 94V		
		Wheel size	16 × 6JJ	17 × 6.5JJ , 16 × 6JJ ^{*3}	17 × 6.5JJ		
		Offset mm	46	38 , 46 ^{*3}	38		

NOTE:

^{*1}: Vehicles with roof rails.

^{*2}: Difference between right and left wheels must be less than 30'.

^{*3}: Indicates optional item.

Items		CU5W		
		XNHYZL6	XRHYZL6	
Vehicle dimension mm	Overall length	4,545		
	Overall width	1,780		
	Overall height (unladen)	1,620/1,670 ^{*1}		
	Wheelbase	2,625		
	Track	Front	1,510	
		Rear	1,520	
	Front overhang	945		
	Rear overhang	975		
	Ground clearance (unladen)	195		
Vehicle wheel alignment	Front	Toe-in (at the centre of tyre tread) mm	1 ± 2	
		Toe angle (per wheel)	0°03' ± 05'	
		Toe-out angle on turns (inner wheel outer wheel at 20°)	22°00' ±1° 30'	
		Camber	- 0°10' ± 30' ^{*2}	
		Caster	3°15' ± 30' ^{*2}	
		Kingpin inclination angle	12°25' ± 1°30'	
		Side slip (per 1m) mm	0 ± 3	
	Steering angle	Inner wheels	34°50' ± 1°30'	
		Outer wheels (reference)	29°20'	
	Rear	Toe-in (at the centre of tyre tread) mm	3 ± 2	
		Toe angle (per wheel)	0°08' ± 05'	
		Camber	- 0°40' ± 30' ^{*2}	
Wheels and tyres		Tyre size	215/55R17 94V , 215/60R16 95H ^{*3}	
		Wheel size	17 × 6.5JJ , 16 × 6JJ ^{*3}	
		Offset mm	38 , 46 ^{*3}	

NOTE:

^{*1}: Vehicles with roof rails.^{*2}: Difference between right and left wheels must be less than 30'.^{*3}: Indicates optional item.