

SECTION PD

MODIFICATION NOTICE:
Service Data and Specifications have been changed.

CONTENTS

SERVICE DATA AND SPECIFICATIONS (SDS)	4002	Final Drive.....	4002
---	------	------------------	------

GENERAL SPECIFICATIONS

Body type	Wagon									
Engine	TB45E		TB48DE		ZD30DDTi		TD42			
Transmission	5M/T		5A/T		5M/T		4A/T			
Front final drive	Standard									
	H233B									
	2-pinion									
Gear ratio	4.111		4.375		3.545		4.111		4.375	
Number of teeth (Drive gear/drive pinion)	37/9		35/8		39/11		37/9		35/8	
Oil capacity (Approx.) ℓ (Imp pt)	5.4 (9-1/2)									
Rear final drive [Grade]	Standard	Optional		Standard	Optional	Standard	Optional	Standard	Standard	Standard
	H233B		H260		H233B		H233B			
	4-pinion	LSD	Diff. lock	4-pinion	Diff. lock	4-pinion	Diff. lock	LSD	Diff. lock	4-pinion
Gear ratio	4.111		4.375		3.545		4.111		4.375	
Number of teeth (Drive gear/drive pinion)	37/9		35/8		39/11		37/9		35/8	
Oil capacity (Approx.) ℓ (Imp pt)	2.4 (4-1/4)	2.1 (3-3/4)	3.0 (5-1/4)	4.7 (8-1/4)	3.7 (6-1/2)	2.4 (4-1/4)	3.0 (5-1/4)	2.1 (3-3/4)	3.0 (5-1/4)	2.4 (4-1/4)

Final Drive

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive (Cont'd)

Body type	Hardtop			
Engine	TB45E	ZD30DDTi		
Transmission	5M/T	5M/T	4A/T	
Front final drive	Standard			
	H233B			
	2-pinion			
Gear ratio	4.111		4.375	
Number of teeth (Drive gear/drive pinion)	37/9		35/8	
Oil capacity (Approx.) ℓ (Imp pt)	5.4 (9-1/2)			
Rear final drive [Grade]	Standard	Optional	Standard	Optional
	H233B			
	4-pinion	Diff. lock	LSD	Diff. lock
Gear ratio	4.111			
Number of teeth (Drive gear/drive pinion)	37/9			
Oil capacity (Approx.) ℓ (Imp pt)	2.4 (4-1/4)	3.0 (5-1/4)	2.1 (3-3/4)	3.0 (5-1/4)