

BODY AND EXTERIOR

5-1

	Page
S SERVICE DATA AIRBAG	2
1. Supplemental Restraint System "Airbag"	2
2. Body Datum Points	2
3. Datum Dimensions.....	17
4. Datum Points and Dimensions Concerning On-Board Aiming Adjustment.....	25
C COMPONENT PARTS	26
1. Front Hood and Hood Lock	26
2. Trunk Lid	27
3. Front Bumper	28
4. Rear Bumper.....	29
5. Sunroof.....	30
6. Steering Support Beam	31
7. Guard Pipe.....	32
W SERVICE PROCEDURE	33
1. Hood.....	33
2. Trunk Lid	35
3. Fuel Flap	36
4. Front Bumper	37
5. Rear Bumper.....	38
6. Coating Method for PP Bumper	40
7. Repair Instructions for Colored PP Bumper	41
8. Side Protector	45
9. Front Fender	46
10. Mud Guard and Arch Protector	47
11. Cowl Panel	47
12. Molding and Retainer.....	48
13. Front Grille	48
14. Sunroof.....	48
15. Rear Spoiler	52
K DIAGNOSTICS	54
1. Sunroof.....	54

1. Supplemental Restraint System "Airbag"

Airbag system wiring harness is routed on and along body panels.

CAUTION:

- All Airbag system wiring harness and connectors are colored yellow. Do not use electrical test equipment on these circuit.
- Be careful not to damage Airbag system wiring harness when repairing the body panel.

2. Body Datum Points


Various master repair locations are established as datum points used during body repairs. In addition, guide holes, locators and indents are provided to facilitate panel replacement and achieve alignment accuracy.

NOTE:

Left and right datum points are all symmetrical to each other.


A: ENGINE COMPARTMENT AND ROOM

1. SEDAN AND WAGON



①	Radiator panel (UPR) repair bolt hole M8 (Right)	⑯	Wax coat hole, 20 mm (0.79 in) dia. (Symmetrical)
②	Radiator panel (UPR) repair bolt hole M8 (Left)	⑯	Retainer attaching square hole 7 mm (0.28 in) (Symmetrical)
③	Fender attaching bolt hole M6 (Symmetrical)	⑰	Sun visor attaching hole 20 mm (0.79 in) dia. (Symmetrical)
④	Headlight attaching bolt hole M6 (Symmetrical)	⑱	Retainer attaching square hole 7 mm (0.28 in) (Symmetrical)
⑤	Radiator panel side gauge hole 24 mm (0.94 in) dia. (Symmetrical)	⑲	Retainer attaching square hole 7 mm (0.28 in) (Symmetrical)
⑥	Front bumper mounting hole 14 x 17 mm (0.55 x 0.67 in) dia. (Symmetrical)	⑳	Center pillar gauge hole 10 mm (0.39 in) dia. (Symmetrical)
⑦	Front crossmember attaching bolt hole 12.4 mm (0.488 in) dia. (Symmetrical)	㉑	Belt anchor attaching bolt hole (Symmetrical)
⑧	Fender attaching bolt hole M6 (Symmetrical)	㉒	Wax coat hole, 20 mm (0.79 in) dia. (Symmetrical)
⑨	Front strut mounting hole 10 mm (0.39 in) dia. (Symmetrical)	㉓	Rear door switch attaching hole 20 mm (0.79 in) dia. (Symmetrical)
⑩	Hood hinge attaching bolt hole M8 (Symmetrical)	㉔	Retainer attaching square hole 7 mm (0.28 in) (Symmetrical)
⑪	Cowl panel mounting hole 5 mm (0.20 in) dia. (Located in center of vehicle.)	㉕	Spare tire attaching bolt hole M8
⑫	Front rail (Inner) mirror attaching bolt hole 8 mm (0.31 in) dia.	㉖	Air draw hole 7 mm (0.28 in) dia. (Symmetrical)
⑬	Fender attaching bolt hole M6 (Symmetrical)	㉗	Fender attaching bolt hole M6 (Symmetrical)
⑭	Front pillar gauge hole 20 mm (0.79 in) dia. (Symmetrical)	㉘	Door switch attaching hole 20 mm (0.79 in) dia. (Symmetrical)
		㉙	Front glass attaching hole Right 6.5 mm (0.256 in) dia. Left 6.5 x 10 mm (0.256 x 0.39 in) dia.


2. COUPE



① Radiator panel (UPR) repair bolt hole M8 (Right)	⑯ Retainer attaching square hole 7 mm (0.28 in) (Symmetrical)
② Radiator panel (UPR) repair bolt hole M8 (Left)	⑰ Sun visor attaching hole 20 mm (0.79 in) dia. (Symmetrical)
③ Fender attaching bolt hole M6 (Symmetrical)	⑲ Spare tire attaching bolt hole M8
④ Headlight attaching bolt hole M6 (Symmetrical)	⑳ Air draw hole 7 mm (0.28 in) dia. (Symmetrical)
⑤ Radiator panel side gauge hole 24 mm (0.94 in) dia. (Symmetrical)	⑶ Fender attaching bolt hole M6 (Symmetrical)
⑥ Front bumper mounting hole 14 x 17 mm (0.55 x 0.67 in) dia. (Symmetrical)	⑷ Front glass attaching hole Right 6.5 mm (0.256 in) dia. Left 6.5 x 10 mm (0.256 x 0.39 in) dia.
⑦ Front crossmember attaching bolt hole 12.4 mm (0.488 in) dia. (Symmetrical)	⑹ Wax coat hole 20 mm (0.79 in) dia. (Symmetrical)
⑧ Fender attaching bolt hole M6 (Symmetrical)	⑺ Door switch attaching hole 13.5 mm (0.531 in) dia. (Symmetrical)
⑨ Front strut mounting hole 10 mm (0.39 in) dia. (Symmetrical)	⑻ Retainer attaching square hole 8 mm (0.31 in). (Symmetrical)
⑩ Hood hinge attaching bolt hole M8 (Symmetrical)	⑼ Rear quarter glass attaching hole 8 mm (0.31 in) dia. (Symmetrical)
⑪ Cowl panel mounting hole 5 mm (0.20 in) dia. (Located in center of vehicle.)	⑽ Rear quarter glass attaching hole 7 mm (0.28 in) dia. (Symmetrical)
⑫ Front rail (Inner) mirror attaching bolt hole 8 mm (0.31 in) dia.	⑾ Rear quarter glass attaching hole 8 x 5.5 mm (0.31 x 0.217 in) dia. (Symmetrical)
⑬ Fender attaching bolt hole M6 (Symmetrical)	⑿ Retainer attaching square hole 8 mm (0.31 in). (Symmetrical)
⑭ Front pillar gauge hole 20 mm (0.79 in) dia. (Symmetrical)	⑯ Seat belt anchor attaching bolt hole 16 mm (0.63 in) dia. (Symmetrical)

B: LUGGAGE COMPARTMENT AND ROOM

1. SEDAN AND COUPE




◎ : Master repair location

G5M0111

- ㉗ Rear pillar (Inner) gauge hole 8 mm (0.31 in) dia. (Symmetrical)
- ㉘ Rear roof trim attaching hole 8 mm (0.31 in) dia. (Symmetrical)
- ㉙ Rear quarter trim attaching hole 8 mm (0.31 in) dia. (Symmetrical)
- ㉚ Seat belt anchor attaching bolt hole (Symmetrical)
- ㉛ Reinforcement (Rear panel rear) repair locator (Located in center of vehicle)
- ㉜ Rear corner patch at flange (Symmetrical)
- ㉝ Rear skirt (UPR) cutout (Repair locator)
- ㉞ Rear skirt gauge hole 20 mm (0.79 in) dia. (Symmetrical)
- ㉟ Rear combination light mounting hole 9 mm (0.35 in) dia. (Symmetrical)
- ㉟ Rear quarter bumper side gauge hole 20 mm (0.79 in) dia. (Left)
- ㉞ Rear quarter bumper side gauge hole 20 mm (0.79 in) dia. (Right)
- ㉟ Instrument panel attaching square hole 22 x 34.5 mm (0.87 x 1.358 in) (Right)
- ㉞ Steering support beam attaching bolt hole M8 (Symmetrical)
- ㉟ Front pillar (Inner) gauge hole 10 mm (0.39 in) dia. (Symmetrical)
- ㉛ Floor mat attaching clip hole 8 mm (0.31 in) dia. (Symmetrical)
- ㉟ Rear panel (Center) repair locator (Located in center of vehicle.)
- ㉞ Rear glass attaching hole (Right): 6.5 mm (0.256 in) dia. (Left): 6.5 x 10 mm (0.256 x 0.39 in) dia.


2. WAGON



G5M0113

- ④② Rear quarter glass attaching hole 8 mm (0.31 in) dia. (Symmetrical)
- ④③ Roof rail attaching hole 10 mm (0.39 in) dia. (Symmetrical)
- ④④ Rear quarter glass attaching hole 8 x 15 mm (0.31 x 0.59 in) dia. (Symmetrical)
- ④⑤ Rear roof trim attaching hole 8 mm (0.31 in) dia. (Symmetrical)
- ④⑥ Rear strut mounting hole 10 mm (0.39 in) dia. (Symmetrical)
- ④⑦ Rear gate stay attaching bolt hole M8 (Symmetrical)
- ④⑧ Child seat anchor attaching bolt hole
- ④⑨ Rear combination light mounting hole 10 mm (0.39 in) dia. (Symmetrical)
- ④⑩ Side rail (Inner) gauge hole 8 mm (0.31 in) dia. (Symmetrical)
- ④⑪ Rear quarter trim attaching hole 8 mm (0.31 in) dia. (Symmetrical)
- ④⑫ Rear quarter harness attaching clip hole 7 mm (0.28 in) dia. (Symmetrical)
- ④⑬ Seat belt anchor attaching bolt hole (Symmetrical)


C: UNDER BODY




G5M0112

- ⑩ Radiator panel (LWR) frame gauge hole 15 mm (0.59 in) dia. (Symmetrical)
- ⑪ Front side frame gauge hole 20 mm (0.79 in) dia. (Symmetrical)
- ⑫ Front crossmember attaching hole 12.4 mm (0.488 in) dia. (Symmetrical)
- ⑬ Front suspension attaching bolt hole M14
- ⑭ Side frame gauge hole 20 mm (0.79 in) dia. (Symmetrical)
- ⑮ Transmission mount attaching bolt hole M10 (Symmetrical)
- ⑯ Side frame gauge hole 15 mm (0.59 in) dia. (Symmetrical)
- ⑰ Rear differential attaching bolt hole M12 (Symmetrical)
- ⑱ Rear suspension attaching bolt hole M12 (Symmetrical)
- ⑲ Rear side frame gauge hole 15 mm (0.59 in) dia. (Symmetrical)


D: DATUM POINT LOCATION




G5M0114




G5M0207




G5M0208




G5M0209




G5M0210




G5M0211




G5M0212




G5M0213




G5M0214




G5M0215




G5M0216




G5M0217




G5M0218




G5M0219




G5M0220




G5M0221




G5M0222




G5M0223




G5M0224




G5M0225




G5M0226




G5M0227




G5M0228




G5M0229




G5M0230

Sedan


G5M0231




G5M0232

Sedan


G5M0233




G5M0234

Sedan


G5M0235




G5M0236

Sedan


G5M0237




G5M0238




G5M0239




G5M0240




G5M0241




G5M0242



G5M0243




G5M0244




G5M0245

Wagon




G5M0246




G5M0247

Wagon




G5M0248

Wagon




G5M0249


Wagon




G5M0250




G5M0251




G5M0252




G5M0253




G5M0254




G5M0255




G5M0256




G5M0257




G5M0258




G5M0259




G5M0260




G5M0261




G5M0262




G5M0263




G5M0264




G5M0265




H5M0670A




G5M0266




G5M0268




G5M0269




G5M0644




G5M0645




G5M0646




G5M0647



G5M0648




G5M0649



G5M0650

SUBARU.




3. Datum Dimensions

Use a tram tracking gauge to measure all dimensions. If a measuring tape is used, be extremely careful because it tends to deflect or twist, which results in a false reading.

NOTE:

- A suffix character "R" or "L" refers to the right or the left.
- All dimensions refer to the distance between the centers of holes measured in a straight line.
- Each dimension indicates a projected dimension between hole centers.

A: FRONT STRUCTURE





G5M0123


Unit: mm (in)

(11)	—	(9) R	—	(9) L	—	525 (20.67)
(11)	—	(6) R	—	(6) L	—	988 (38.90)
(11)	—	(3) R	—	(3) L	—	990 (38.98)
(10) R	—	(3) R	—	(3) L	—	829 (32.64)
(10) L	—	(8) R	—	(8) L	—	567 (22.32)
(6) R	—	(3) R	—	(3) L	—	264 (10.39)
(6) L	—	(10) R	—	(10) L	—	942 (37.09)
(10) R	—	(11) R	—	(11) L	—	1,382 (54.41)
(10) L	—	(11) R	—	(11) L	—	1,336 (52.60)
(5) R	—	(4) R	—	(4) L	—	942 (37.09)
(5) L	—	(4) R	—	(4) L	—	1,174 (46.22)
(4) R	—	(13) R	—	(13) L	—	1,269 (49.96)
(60) R	—	(13) R	—	(13) L	—	1,113 (43.82)
(60) L	—	(14) R	—	(14) L	—	1,076 (42.36)
(1) — (11)	—	(1) — (11)	—	(1) — (11)	—	882 (34.72)
(2) — (11)	—	(2) — (11)	—	(2) — (11)	—	913 (35.94)

B: CENTER STRUCTURE



G5M0124





G5M0125

G5M0124

C: DOORS AND REAR QUARTER

1. SEDAN AND WAGON




G5M0126

Unit: mm (in)

(14) — (18) : 1,495 (58.86)	(19) — (23) : 912 (35.91)
(13) — (64) : 947 (37.28)	(20) — (36) L : 1,462 (57.56)
(16) — (64) : 976 (38.43)	(20) — (37) R : 1,481 (58.31) } (Wagon)
(20) — (23) : 803 (31.61)	(62) — (43) : 377 (14.84) (Wagon)
(20) — (24) : 829 (32.64)	(42) — (44) : 847 (33.35) (Wagon)

2. COUPE





H5M0713A

Unit: mm (in)

(14)	—	(71)	:	1,576 (62.05)	(73)	—	(75)	:	512 (20.16)
(13)	—	(70)	:	1,251 (49.25)	(70)	—	(36) L	:	1,295 (50.98)
(16)	—	(70)	:	997 (39.25)	(70)	—	(37) R	:	1,243 (48.94)
(13)	—	(69)	:	1,063 (41.85)					
(72)	—	(74)	:	778 (30.63)					

D: FRONT WINDSHIELD AND REAR WINDOW





G5M0127

Unit: mm (in)

(11) — (12) : 989 (38.94)	(66) — (28) R } : 714 (28.11)
(67) R — (67) L : 1,012 (39.84)	(66) — (28) L } :
(11) — (67) R } : 1,116 (43.94)	(66) — (68) R } : 856 (33.70)
(11) — (67) L } :	(66) — (68) L } :
	(68) R — (68) L : 1,012 (39.84)

E: TRUNK LID AND REAR GATE



G5M0128

Unit: mm (in)


TRUNK LID

(31)	—	(32) R	—	(32) L	—	575 (22.64)
(31)	—	(26) R	—	(26) L	—	812 (31.97)
(31)	—	(33)	—		—	522 (20.55)
(31)	—	(35) R	—	(35) L	—	794 (31.26)
(34) R	—	(34) L	—		—	890 (35.04)
(35) R	—	(35) L	—		—	1,364 (53.70)

REAR GATE

(45) R	—	(48)	—	(48)	—	988 (38.90)
(45) L	—	(47) R	—	(47) L	—	926 (36.46)
(47) R	—	(47) L	—	(47) L	—	1,043 (41.06)
(49) R	—	(49) L	—	(49) L	—	1,335 (52.56)
(34) R	—	(34) L	—	(34) L	—	890 (35.04)

F: COMPARTMENT




G5M0651

Unit: mm (in)

(30) R	—	(30) L	:	1,197 (47.13)	(41)	—	(15) R	—	(15) L	:	1,140 (44.88)	(41)	—	(30) R	—	(30) L	:	1,168 (45.98)	(Sedan)
(21) R	—	(21) L	:	1,061 (41.77)	(41)	—	(22) R	—	(22) L	:	733 (28.86)	(41)	—	(28) R	—	(28) L	:	1,050 (41.34)	(Sedan)
(15) R	—	(15) L	:	1,453 (57.20)	(41)	—	(12) R	—	(12) L	:	1,156 (45.51)	(41)	—	(21) R	—	(21) L	:	1,038 (40.87)	
(22) R	—	(22) L	:	1,453 (57.20)	(41)	—	(27) R	—	(27) L	:	1,085 (42.72)	(41)	—	(17) R	—	(17) L	:	1,208 (47.56)	
(39) R	—	(39) L	:	1,388 (54.65)	(41)	—	(26) R	—	(26) L	:	1,568 (61.73)	(41)	—	(33)	—	(33)	:	1,569 (61.77)	(Sedan)
(40) R	—	(40) L	:	1,401 (55.16)	(41)	—	(25)	—	(25)	:	1,184 (46.61)	(76) R	—	(76) L	—	(76) L	:	1,212 (47.72)	(Coupe)
(41)	—	(38)	:	1,527 (60.12)	(41)	—	(39) R	—	(39) L	:	1,524 (60.00)	(41)	—	(40) R	—	(40) L	:	1,756 (69.13)	

G: LUGGAGE ROOM




G5M0130

Unit: mm (in)

(41) — (65) R } : 1,122 (44.17)	(41) — (43) R } : 1,237 (48.70)
(41) — (65) L } : 1,225 (48.23)	(41) — (43) L } : 971 (38.23)
(41) — (45) R } : 1,225 (48.23)	(48) — (46) R } : 971 (38.23)
(41) — (45) L } : 1,446 (56.93)	(48) — (46) L } : 1,235 (48.62)
(41) — (48) : 1,446 (56.93)	(65) R — (65) L : 1,235 (48.62)

4. Datum Points and Dimensions Concerning On-Board Aiming Adjustment


If headlight aiming is misaligned due to damaged body panel, repair headlight mating surface using body and headlight datum points as a guide.



Unit: mm (in)

$(\textcircled{11})$	—	$(\textcircled{A})_L$	$\}$:	993 (39.09)
$(\textcircled{11})$	—	$(\textcircled{A})_R$	$\}$:	1,048 (41.26)

1. Front Hood and Hood Lock




H5M0671A

(1) Front hood	(7) Hood lock ASSY
(2) Hinge (RH, LH)	(8) Striker
(3) Hood hinge cover (RH, LH)	(9) Front hood stay
(4) Lever ASSY	(10) Seal (Front hood) SD
(5) Cable	(11) Seal (Front hood) CTR
(6) Stopper	

Tightening torque: N·m (kg·m, ft·lb)T1: 14 ± 9 (1.4±0.9, 10.1±6.5)T2: 32 ± 1 (3.3±0.1, 23.9±0.7)

2. Trunk Lid




G5M0133

① Torsion bar
② Trunk lid
③ Weatherstrip
④ Rod
⑤ Trunk lid lock ASSY

⑥ Striker
⑦ Hinge ASSY

Tightening torque: N·m (kg·m, ft·lb)
T1: 14±4 (1.4±0.4, 10.1±2.9)
T2: 18±5 (1.8±0.5, 13.0±3.6)

3. Front Bumper



H5M0716A

① Plate

② Bumper face

③ Spacer

④ E/A from bumper


⑤ Front beam

⑥ Bracket (Side)

⑦ Holder upper

Tightening torque: N·m (kg·m, ft·lb)T: 93 ± 25 (9.5±2.5, 69±18)

4. Rear Bumper




H5M0715A

- ① Holder upper
- ② Bumper beam
- ③ Bracket (Side)
- ④ E/A from bumper

- ⑤ Plate
- ⑥ Bumper surface

Tightening torque: N·m (kg·m, ft·lb)
T: 93±25 (9.5±2.5, 69±18)

5. Sunroof



G5M0136


- ① Weatherstrip
- ② Sunroof panel
- ③ Rear guide ASSY
- ④ Lower panel
- ⑤ Lower panel
- ⑥ Rear guide ASSY
- ⑦ Drive unit
- ⑧ Relay
- ⑨ Harness

- ⑩ Harness
- ⑪ Sunroof trim
- ⑫ Guide rail
- ⑬ Set bracket
- ⑭ Guide rail
- ⑮ Motor ASSY
- ⑯ Sealed tape
- ⑰ Frame ASSY
- ⑱ Sealed cushion

- ⑲ Shutting ASSY (RH)
- ⑳ Shutting ASSY (LH)
- ㉑ Drain tube
- ㉒ Garnish

Tightening torque: N·m (kg·m, ft·lb)
T: 7.4±2.0 (0.75±0.2, 5.4±1.4)

6. Steering Support Beam




G5M0184

① Bracket
② Steering beam

Tightening torque: N·m (kg·m, ft·lb)
T: 18±5 (1.8±0.5, 13.0±3.6)

7. Guard Pipe



B5M0371A

① Guard pipe
② Rear floor panel

Tightening torque: N·m (kg·m, ft·lb)
T: 32 ± 10 (3.3 ± 1.0 , 23.9 ± 7)

1. Hood

A: REMOVAL AND INSTALLATION





NOTE:

The hood lock has a dual locking design which consists of a main lock and a safety lock mechanism. When the release knob located at the front pillar on the driver's side is pulled back, the main lock is released through the cable attached to the knob.

The safety lock can be released by pushing the lever protruding above the front grill while opening the hood.

1. HOOD

- 1) Open front hood, and remove washer hose.
- 2) Remove attaching bolts.
- 3) Detach front hood from hinges.



- 4) Installation is in the reverse order of removal.

CAUTION:

Adjust buffer assembly on each end so that main lock is applied securely when hood is released from a height of approx. 20 mm (0.79 in).

NOTE:


Align the center of striker with lock during installation. Make sure safety lever is properly caught by striker under the hood's own weight.

2. HOOD LOCK

- 1) Open front hood and remove front grille.
- 2) Remove bolts which secure lock assembly to radiator panel, and remove lock assembly.
- 3) Disconnect release cable from lock assembly.
- 4) Installation is in the reverse order of removal.


NOTE:

- Route hood lock release cable and hold with clips.
- After installing release cable, ensure it operates smoothly.
- Apply grease to sliding surfaces of parts.




3. RELEASE CABLE

- 1) Remove front grille.
- 2) Remove release cable from lock assembly.
- 3) Remove cable clip from engine compartment.
- 4) Remove bracket from front pillar.
- 5) Installation is in the reverse order of removal.



B: POINTS TO CHECK

- 1) Check striker for bending or abnormal wear.
- 2) Check safety lever for improper movement.
- 3) Check other levers and spring for rust formation and unsmooth movement.



C: ADJUSTMENT


- 1) Fore-aft and left-right adjustments
Loosen striker mounting bolts and adjust fore-and-aft position of striker.

CAUTION:

Do not adjust striker position using the lock. Doing so may result in a misaligned front grille.

- 2) Up-down adjustment

Make up-and-down adjustment of striker only when hood does not properly contact buffer or hood is not flush with fender, or when release cable does not properly operate. Adjustment can be made by adjusting the stroke length of striker after lock assembly mounting screws are removed.




2. Trunk Lid

A: REMOVAL AND INSTALLATION

1. TRUNK LID

- 1) Open trunk lid.
- 2) Remove trunk lid mounting bolts and detach trunk lid from hinges.
- 3) Installation is in the reverse order of removal.



2. TORSION BAR

- 1) Open trunk lid. Remove torsion bars from hinge links using ST.

ST 927780000 REMOVER

CAUTION:

Be careful because torsion bar quickly swings back when released.

- 2) Remove the left and right torsion bars.


WARNING:

Be careful because trunk lid drops under its own weight when torsion bars are removed.

- 3) Installation is in the reverse order of removal.

NOTE:

Apply a coat of grease to the rotary section of hinges and contact surfaces of torsion bars.



3. TRUNK LID LOCK ASSEMBLY AND KEY CYLINDER

- 1) Remove rod of lock assembly from rod holder of key lock assembly.

- 2) Remove bolts which hold lock assembly and remove lock assembly.


NOTE:

- Always remove rear skirt trim panel beforehand, if so equipped.

- Be careful not to bend opener cable.

- 3) Remove clip and detach key cylinder from trunk lid.


- 4) Installation is in the reverse order of removal.



G5M0148

NOTE:

Apply grease to sliding surfaces of lock assembly and striker.



G5M0147

4. TRUNK LID OPENER

- 1) Remove driver's seat, rear seats, center pillar lower cover, floor mat, rear arch cover and side sill cover (on the driver's side).
- 2) Remove all clips which hold cable.
- 3) Disconnect cable from pull handle assembly.
- 4) Remove bolts and detach pull handle assembly.
- 5) Loosen bolts which hold lock assembly, and remove it.
- 6) Remove striker from trunk lid.
- 7) Disconnect cable from striker.

NOTE:

Be careful not to bend or break cable.


- 8) Installation is in the reverse order of removal.

CAUTION:

- When installing cover to pull handle assembly, observe the following:
 - Be careful not to catch harness.
 - Engage pull handle assembly pawls firmly.

NOTE:


After installing opener cable, ensure it moves smoothly.



G5M0149

B: ADJUSTMENT**1. TRUNK LID**

- 1) To adjust left-right lid positioning, loosen bolts which hold trunk lid to hinges.
- 2) To adjust up-down lid alignment, place washer(s) between trunk lid and hinges or move trunk lock assembly up or down.




G5M0150

3. FUEL FLAP**A: REMOVAL AND INSTALLATION****1. FUEL FLAP**

- 1) Remove bolts which hold hinge to car body, and detach fuel flap and hinge as a unit.
- 2) Installation is in the reverse order of removal.

CAUTION:

Make sure the clearance between fuel flap and car body is equal at all points.




2. FUEL FLAP OPENER

- 1) Remove driver's seat, rear seats, center pillar lower cover, floor mat, rear arch cover/rear quarter trim (wagon), and side sill cover (on the driver's side).
- 2) Remove all clips which hold cable.
- 3) Disconnect cable from pull handle.
- 4) Detach pull handle by removing bolts.
- 5) Detach fuel lock holder by turning it.
- 6) Installation is in the reverse order of removal.

CAUTION:

- When installing cover to pull handle assembly, observe the following:
 - Be careful not to catch harness.
 - Engage pull handle assembly pawls firmly.
- After installing opener cable, ensure it moves smoothly.




4. Front Bumper


A: REMOVAL AND INSTALLATION


- 1) Disconnect the ground cable from the battery.
- 2) Remove the canister.
- 3) Remove the front grille.
- 4) Remove the parking light and headlight LH.
- 5) Remove the mud guard.
- 6) Remove bolts from side of bumper.

7) Remove bolt from lower center of bumper.




8) Remove bolts from lower side of bumper.






G5M0156

- 9) Remove bolts (engine compartment side) from bumper stays.
- 10) Remove turn signal light connector.



G5M0157

- 11) Remove bumper assembly.



G5M0158

- 12) Installation is in the reverse order of removal.

CAUTION:


- Be extremely careful to prevent scratches on bumper face as it is made of resin.
- Be careful not to scratch the body when removing or installing the bumper.
- To facilitate installation of front bumper, attach hook (located at stay) to body panel.
- When installing canister, insert air vent hose of canister into the hole on body.

5. Rear Bumper

A: REMOVAL AND INSTALLATION


1. SEDAN

- 1) Open trunk lid. Remove trunk trim panel clips and detach trim.
- 2) Disconnect license plate light connector.
- 3) Remove bolts from side of bumper.




G5M0160


- 4) Remove bolts from bumper stay.



G5M0161



5) Remove rear bumper.




6) Installation is in the reverse order of removal.

CAUTION:

- Be extremely careful to prevent scratches on bumper face as it is made of resin.
- Be careful not to scratch the body when removing or installing bumper.
- To facilitate installation of rear bumper, attach hook (located at stay) to body panel.

2. WAGON

- 1) Open rear gate and rear quarter trim lid.
- 2) Disconnect license plate light connector.
- 3) Remove bolts from side of bumper.
- 4) Remove bolts from bumper stays.
- 5) Remove bumper assembly.




6) Installation is in the reverse order of removal.

CAUTION:

- Be extremely careful to prevent scratches on bumper face as it is made of resin.
- Be careful not to scratch the body when removing or installing bumper.
- To facilitate installation of rear bumper, attach hook (located at stay) to body panel.

6. Coating Method for PP Bumper

A: PROCESS STEPS

Process No.	Process name	Job contents	
1	Bumper mounting	Set bumper on paint worktable if required. Use paint worktable conforming to inner shape of bumper when possible.	 G5M0164
2	Masking	Mask specified part (black base) with masking tape. Use masking tape for PP (example, Nichiban No. 533, etc.).	
3	Degreasing, cleaning	Clean all parts to be painted with white gasoline, normal alcohol, etc. to remove dirt, oil, fat, etc.	
4	Primer paint	Apply primer one to all parts to be painted, using air gun. Use primer (clear).	
5	Drying	Dry at normal temperature [10 to 15 min. at 20°C (68°F)]. In half-dried condition, PP primer paint is dissolved by solvent, e.g. thinner, etc. Therefore, if dust or dirt must be removed, use ordinary alcohol, etc.	
6	Top coat paint (I)	Solid color	Metallic color
		Use section (block) paint for top coat. <ul style="list-style-type: none"> Paint in use (for each color): Solid paint Hardener PB Thinner T-301 Mixing ratio: Main agent vs. hardener = 4:1 Viscosity: 10 — 13 sec/20°C (68°F) Film thickness: 35 — 45μ Spraying pressure: 245 — 343 kPa (2.5 — 3.5 kg/cm², 36 — 50 psi) 	Use section (block) paint for top coat. <ul style="list-style-type: none"> Paint in use (for each color): Metallic paint Hardener PB Thinner T-306 Mixing ratio: Main agent vs. hardener = 10:1 Viscosity: 10 — 13 sec/20°C (68°F) Film thickness: 15 — 20μ Spraying pressure: 245 — 343 kPa (2.5 — 3.5 kg/cm², 36 — 50 psi)
7	Drying	Not required.	Dry at normal temperature [10 min. or more at 20°C (68°F)]. In half-dried condition, avoid dust, dirt.
8	Top coat paint (II)	Not required.	Apply a clear coat to parts with top coat paint (I), three times, at 5 — 7 minute intervals. <ul style="list-style-type: none"> Paint in use Metallic paint Hardener PB Thinner T-301 Mixing ratio: Clear vs. hardener = 6:1 Viscosity: 14 — 16 sec/20°C (68°F) Film thickness: 25 — 30μ Spraying pressure: 245 — 343 kPa (2.5 — 3.5 kg/cm², 36 — 50 psi)
9	Drying	60°C (140°F), 60 min. or 80°C (176°F), 30 min. If higher than 80°C (176°F), PP may be deformed. Keep maximum temperature of 80°C (176°F).	
10	Inspection	Paint check.	
11	Masking removal	Remove masking in process No. 2.	

7. Repair Instructions for Colored PP Bumper

All PP bumpers are provided with a grained surface, and if the surface is damaged, it cannot normally be restored to its former condition. Damage limited to shallow scratches that cause only a change in the lustre of the base material or coating, can be almost fully restored. Before repairing a damaged area, explain this point to the customer and get an understanding about the matter.

Repair methods are outlined below, based on a classification of the extent of damage.

A: MINOR DAMAGE CAUSING ONLY A CHANGE IN THE LUSTRE OF THE BUMPER DUE TO A LIGHT TOUCH

Almost restorable.

Process No.	Process name	Job contents	
1	Cleaning	Clean the area to be repaired using water.	
2	Sanding	Grind the repairing area with #500 sandpaper in a "feathering" motion.	
3	Finish	Resin section	Coated section
		Repeatedly apply wax to the affected area using a soft cloth (such as flannel). Recommended wax: NITTO KASEI Soft 99 TIRE WAX BLACK, or equivalent.	Perform either the same operation as for the resin section or process No. 18 and subsequent operations in the "(3)" section, depending on the degree and nature of damage.
		Polish the waxed area with a clean cloth after 5 to 10 minutes.	

B: DEEP DAMAGE CAUSED BY SCRATCHING FENCES, ETC.




A dent cannot be repaired but a whitened or swelled part can be removed.



Process No.	Process name	Job contents	
1	Cleaning	Clean damaged area with water.	
2	Removal of damaged area	Cut off protruding area, if any, due to collision, using a putty knife.	
3	Sanding	Grind the affected area with #100 to #500 sandpaper.	
4	Finish	Resin section	Coated section
		Same as Process No. 3 in the "(1)" section.	Perform Process No. 12 and subsequent operations in the "(3)" section.

C: DEEP DAMAGE SUCH AS A BREAK OR HOLE THAT REQUIRES FILLING


Much of the peripheral grained surface must be sacrificed for repair, and the degree of restoration is not really worth the expense. (The surface, however, will become almost flush with adjacent areas.)

Recommended repair kit: PP Part Repair Kit (NRM)

Process No.	Process name	Job contents	
1	Bumper removal	Remove bumper as required.	
2	Part removal	Remove parts built into bumper as required.	
3	Bumper placement	Place bumper on a paint worktable as required. It is recommended that contour of worktable accommodate internal shape of bumper.	 G5M0164
4	Surface preparation	Remove dust, oil, etc. from areas to be repaired and surrounding areas, using a suitable solvent (NRM No. 900 Precleno, white gasoline, or alcohol).	
5	Cutting	If nature of damage is cracks or holes, cut a guide slit of 20 to 30 mm (0.79 to 1.18 in) in length along the crack or hole up to the bumper's base surface. Then, bevel or "vee-out" the affected area using a knife or grinder.	 Unit: mm (in)
6	Sanding (I)	Grind beveled surface with sandpaper (#40 to #60) to smooth finish.	
7	Cleaning	Clean the sanded surface with the same solvent as used in Process No. 4.	
8	Temporary welding	Grind the side just opposite the beveled area with sandpaper (#40 to #60) and clean using a solvent. Temporarily spot-weld the side, using a PP welding rod and heater gun.	
		NOTE: <ul style="list-style-type: none"> Do not melt welding rod until it flows out. This results in reduced strength. Leave the welded spot unattended until it cools completely. 	G5M0166

Process No.	Process name	Job contents
9	Welding	<p>Using a heater gun and PP welding rod, weld the beveled spot while melting the rod and damaged area.</p>   <p>NOTE: • Melt the sections indicated by hatched area. • Do not melt welding rod until it flows out, in order to provide strength. • Always keep the heater gun 1 to 2 cm (0.4 to 0.8 in) away from the welding spot. • Leave the welded spot unattended until it cools completely.</p> <p>G5M0167</p>
10	Sanding (II)	<p>Remove excess part of weld with a putty knife. If a drill or disc wheel is used instead of the knife, operate it at a rate lower than 1,500 rpm and grind the excess part little by little. A higher rpm will cause the PP substrate to melt from the heat.</p>  <p>G5M0168</p>
11	Masking	<p>Sand the welded spot smooth with #240 sand paper.</p>
12	Cleaning/degreasing	<p>Mask the black substrate section using masking tape. Recommended masking tape: Nichiban No. 533 or equivalent</p>
13	Primer coating	<p>Completely clean the entire coated area, using solvent similar to that used in Process No. 4.</p> <p>Apply a coat of primer to the repaired surface and its surrounding areas. Mask these areas, if necessary. Recommended primer: Mp/ 364 PP Primer NOTE: Be sure to apply one coat of primer at a spraying pressure of 245 to 343 kPa (2.5 to 3.5 kg/cm², 36 to 50 psi) with a spray gun.</p>
14	Leave unattended.	<p>Leave the repaired area unattended at 20°C (68°F) for 10 to 15 minutes until primer is half-dry. NOTE: If dirt or dust comes in contact with the coated area, wipe it off with a cloth dampened with alcohol. (Do not use thinner since the coated area tends to melt.)</p>
15	Primer surfacer coating	<p>Apply a coat of primer surfacer to the repaired area two or three times at an interval of 3 to 5 minutes. Recommended surfacer: • UPS 300 Flex Primer • No. 303 UPS 300 Exclusive hardener • NPS 725 Exclusive Reducer (thinner) • Mixing ratio: 2 : 1 (UPS 300: No. 303) • Viscosity: 12 — 14 sec/20°C (68°F) • Coated film thickness: 40 — 50µ</p>
16	Drying	<p>Allow the coated surface to dry for 60 minutes at 20°C (68°F) [or 30 minutes at 60°C (140°F)].</p>
17	Sanding (III)	<p>Sand the coated surface and its surrounding areas using #400 sandpaper and water.</p>

Process No.	Process name	Job contents	
18	Cleaning/degreasing	Same as Process No. 12.	
19	Top coat (I)	Solid color	Metallic color
		Use a "block" coating method. <ul style="list-style-type: none"> Recommended paint: Suncryl (SC) No. 307 Flex Hardener SC Reducer (thinner) Mixing ratio: 3 : 1 (Suncryl: No. 307) Viscosity: 11 — 13 sec/20°C (68°F) Coated film thickness: 40 — 50µ Spraying thickness: 245 — 343 kPa (2.5 — 3.5 kg/cm², 36 — 50 psi) 	Use a "block" coating method. <ul style="list-style-type: none"> Recommended paint: Suncryl (SC) No. 307 Flex Hardener SC Reducer (thinner) Mixing ratio: 3 : 1 (Suncryl: No. 307) Viscosity: 11 — 13 sec/20°C (68°F) Coated film thickness: 20 — 30µ Spraying thickness: 245 — 343 kPa (2.5 — 3.5 kg/cm², 36 — 50 psi)
20	Leave unattended.	Not required.	Leave unattended at 20°C (68°F) for at least 10 minutes until the topcoated area is half-dry. NOTE: Be careful to keep dust or dirt from coming in contact with the affected area.
21	Top coat (II)	Not required.	Apply a clear coat three times at an interval of 3 to 5 minutes. <ul style="list-style-type: none"> Recommended paint: SC710 Overlay Clear No. 307 Flex Hardener SC Reducer (thinner) Mixing ratio: 3 : 1 (SC710: No. 307) Viscosity: 10 — 13 sec/20°C (68°F) Coated film thickness: 20 — 30µ Spraying pressure: 245 — 343 kPa (2.5 — 3.5 kg/cm², 36 — 50 psi)
22	Drying	Allow the coated surface to dry at 20°C (68°F) for two hours or 60°C (140°F) for 30 minutes. NOTE: Do not allow the temperature to exceed 80°C (176°F) since this will deform the PP substrate.	
23	Inspection	Carefully check the condition of the repaired area.	
24	Masking removal	Remove masking tape applied in Process No. 11 and 13.	
25	Parts installation	Install parts on bumper in reverse order of removal.	
26	Bumper installation	Install bumper.	




8. Side Protector

A: REMOVAL AND INSTALLATION

NOTE:


Do not re-use protector.



1) Type A and B:

Protector is attached to body with clips.

While holding end of protector by hand, force protector out.



2) Type C:

Protector is attached to body with clips.

Remove door inner trim, and detach protector by pushing clip pawl from inside.

3) Type D:


Protector is attached to body with clips.

While holding end of protector by hand, force protector out.

4) Installation is in the reverse order of removal.

NOTE:

- Type A: Insert clip pins into holes in body, then fit end cap buffers into place.
- Type B: Insert spin weld clips into holes in body, then fit bushings into place.
- Type C and D: Align the clips with holes in body and insert them.
- Install clips in standard holes first.






9. Front Fender

A: REMOVAL AND INSTALLATION

- 1) Disconnect ground cable from battery.
- 2) Remove mud guard.
- 3) Remove parking light and headlight.
- 4) Remove front bumper.
- 5) Remove bolts which secure fender to radiator panel and turn signal light connector.
- 6) Remove body protector. (This step may be skipped if fender is to be reused.)
- 7) Remove attaching bolt to remove fender.

CAUTION:


Be careful not to scratch body panels with fender edges when removing it.



- 8) Installation is in the reverse order of removal.

NOTE:

Check for alignment of front fender with hood and front door with front fender at all points. Adjust, if necessary.



10. Mud Guard and Arch Protector


A: REMOVAL AND INSTALLATION

1. MUD GUARD

- 1) Jack-up vehicle to remove tire.
- 2) Remove screws and clips. Move mud guard toward the center of the body and remove mud guard.
- 3) Installation is in the reverse order of removal.

CAUTION:

Only use new nuts and clips.




2. REAR ARCH PROTECTOR

- 1) Remove clip and screws.
- 2) Remove arch protectors.
- 3) Installation is in the reverse order of removal.

CAUTION:


Only use new nuts and clips.



11. Cowl Panel


A: REMOVAL AND INSTALLATION

- 1) Remove wiper arms.
- 2) Open front hood.
- 3) Pry clip off front hood seal using a screwdriver.
- 4) Lift cowl panel and remove clips from windshield.
- 5) Installation is in the reverse order of removal.



NOTE:


Install middle clip and other clips in that order.



12. Molding and Retainer

A: REMOVAL AND INSTALLATION


- 1) Remove weatherstrip.
- 2) Remove tapping screws.



- 3) Installation is in the reverse order of removal.

NOTE:

Insert clips onto hooks, then fasten with screws.




13. Front Grille

A: REMOVAL AND INSTALLATION

- 1) Remove two upper clips from body panel. To facilitate removal, press portion shown in figure using screwdriver while lightly pulling front grille.
- 2) Installation is in the reverse order of removal.

NOTE:

Attach all clips to grille. Align them with clip hole in body and push them into place.




14. Sunroof


A: REMOVAL

1. SUNROOF PANEL


- 1) Open sunroof approx. 1/3.
- 2) Remove clips attached to front side of sunroof trim by pulling trim from inside of compartment.



- 3) Move trim forward, and detach trim end from holder.




- 4) Detach trim.



- 5) Close sunroof and remove nuts.
- 6) Remove sunroof panel.
- 7) Installation is in the reverse order of removal.


NOTE:

Sunroof trim reference pin must be fitted in holder notch.




2. SUNROOF MOTOR AND RELAY

- 1) Remove roof trim, rear quarter trim, pillar trim, etc. <Ref. to 5-3 [W5A0].>
- 2) Remove screw.
- 3) Disconnect connector.
- 4) Remove relay by pulling it out.




3. SUNROOF FRAME


- 1) Remove roof trim, rear quarter trim, pillar trim, etc. <Ref. to 5-3 [W5A0].>
- 2) Remove sunroof panel.
- 3) Disconnect front and rear drain tubes.




- 4) Disconnect connector between body harness and sunroof harness.




- 5) Loosen two mounting bolts near motor. (Do not remove bolts.)



- 6) Remove six bolts, and four adjusting nuts.




- 7) Remove sunroof frame.
- 8) Loosen set bracket mounting bolt.




B: INSTALLATION


- 1) Insert frame rear end slit to two bolts fitted temporarily to roof brace.



- 2) Align frame to reference pin installed on roof.




- 3) Tighten adjusting nut (that is, set frame at highest position).
Temporarily tighten bolts.



- 4) Install sunroof panel.
- 5) Adjust height by turning adjusting nut.
Also adjust front, rear, right, and left side partitions.


Partition clearance:

$5.9 \pm 0.5 \text{ mm (} 0.232 \pm 0.020 \text{ in)}$




Difference in height between roof panel and sunroof panel:


$0 \pm 1.0 \text{ mm (} 0 \pm 0.039 \text{ in)}$



- 6) Tighten set bracket mounting bolts.



- 7) Tighten bolts.




8) Install drain tubes.

CAUTION:

Insert drain tube securely into drain pipe.

Length: A

Approx. 20 mm (0.79 in)



9) Install roof trim.

10) Install garnish.

NOTE:

Place garnish joint at rear center of body.


11) Install sunroof trim, pillar trim, rear quarter trim etc.

12) Check the following items after assembling all parts;

(1) Garnish must be free from waves.

(2) When sunroof is fully closed, must be no clearance between garnish and sunroof trim.

(3) Sunroof must be free from slack and noise when it is fully opened and closed.




15. Rear Spoiler


A: REMOVAL AND INSTALLATION

1. COUPE

1) Remove stoppers from both sides of trunk lid.



2) Disconnect high-mount stop light connector.



- 3) Remove nuts from rear spoiler.

CAUTION:

Be careful not to drop nuts into box section of trunk lid.

- 4) Lift rear spoiler and unfasten clips.

- 5) Remove spoiler from trunk lid.

CAUTION:

Be careful not to damage trunk lid.

- 6) Installation is in the reverse order of removal.

Tightening torque:

7.4±2.0 N·m (0.75±0.2 kg·m, 5.4±1.4 ft-lb)

1. Sunroof

Entry of water into compartment	<ul style="list-style-type: none"> ① Check roof panel and sunroof panel for improper or poor sealing. ② Check drain tube for clogging. ③ Check sunroof frame seal and body for improper fit.
Booming noise	<ul style="list-style-type: none"> ① Check roof panel and roof panel for improper clearance. ② Check sunroof trim and roof trim for improper clearance.
Abnormal motor noise	<ul style="list-style-type: none"> ① Check motor for looseness. ② Check gears and bearings for wear. ③ Check cable for wear. ④ Check cable pipe for deformities.
Failure of sunroof to operate (Motor operates properly.)	<ul style="list-style-type: none"> ① Check guide rail for foreign particles. ② Check guide rail for improper installation. ③ Check parts for mutual interference. ④ Check cable slider for improper clinching. ⑤ Check cable for improper installation. ⑥ Check clutch adjustment nut for improper tightness.
Motor does not rotate or rotates improperly. (Use sunroof wrench to check operation.)	<ul style="list-style-type: none"> ① Check fuse for blowout. ② Check switch for improper function. ③ Check motor for incorrect terminal voltage. ④ Check relay for improper operation. ⑤ Check poor grounding system. ⑥ Check cords for discontinuity and terminals for poor connections. ⑦ Check limit switch for improper operation.