


GENERAL DESCRIPTION

WHEEL AND TIRE SYSTEM

1. General Description

A: SPECIFICATIONS



(1) Offset

(2) P.C.D.

	Tire size	Rim size	Rim offset mm (in)	P.C.D. mm (in)
Front and rear	P195/60R15 87H	15 × 6JJ	55 (2.17)	100 (3.94) Dia.
	P205/55 R16 89V	16 × 6 1/2JJ		
	215/45 R17 87W	17 × 7JJ		
T-Type tire	T135/70 D16 100M	16 × 4T	50 (1.97)	

	Tire size	Tire inflation pressure kPa (kg/cm ² , psi)
Front and rear	P195/60 R15 87H	Fr: 220 (2.2, 32) Rr: 200 (2.0, 29)
	P205/55 R16 89V	Fr: 220 (2.2, 32) Rr: 200 (2.0, 29)
	215/45 R17 87W	Fr: 230 (2.3, 33) Rr: 220 (2.2, 32)
T-Type tire	T135/70 D16 100M	420 (4.2, 60)

NOTE:

- “T-type” tire for temporary use is supplied as a spare tire.

GENERAL DESCRIPTION

WHEEL AND TIRE SYSTEM

1. SERVICE DATA

Item	Axial runout	Radial runout
Steel wheel	1.5 mm (0.059 in)	
Aluminum wheel	1.0 mm (0.039 in)	

2. ADJUSTING PARTS

Wheel balancing	Standard	Service limit
Dynamic unbalance	Less than 5 g (0.18 oz)	

Balance weight part number (For steel wheel)	Weight
28101TC000	5 g (0.18 oz)
28101SA060	10 g (0.35 oz)
28101SA070	15 g (0.53 oz)
28101SA080	20 g (0.71 oz)
28101SA090	25 g (0.88 oz)
723141340	30 g (1.06 oz)
723141350	35 g (1.23 oz)
723141360	40 g (1.41 oz)
723141370	45 g (1.59 oz)
723241380	50 g (1.76 oz)
723241580	55 g (1.94 oz)
723241590	60 g (2.12 oz)

Balance weight part number (For aluminum wheel)	Weight
28101SA000	5 g (0.18 oz)
28101SA010	10 g (0.35 oz)
28101SA020	15 g (0.53 oz)
28101SA030	20 g (0.71 oz)
28101SA040	25 g (0.88 oz)
23141GA512	30 g (1.06 oz)
23141GA522	35 g (1.23 oz)
23141GA532	40 g (1.41 oz)
23141GA542	45 g (1.59 oz)
23141GA552	50 g (1.76 oz)
—	55 g (1.94 oz)
23141GA572	60 g (2.12 oz)

B: PREPARATION TOOL

1. GENERAL PURPOSE TOOLS

TOOL NAME	REMARKS
Air pressure gauge	Used for measuring tire air pressure.
Dial gauge	Used for measuring wheel runout.