

# Fuel System Trouble in General

## FUEL INJECTION (FUEL SYSTEMS)

### 33. Fuel System Trouble in General

#### A: INSPECTION

Trouble and possible cause		Corrective action
<b>1. Insufficient fuel supply to injector</b>		
1)	Fuel pump does not operate.	
	<input type="radio"/> Defective terminal contact	Inspect contact, especially ground, and tighten it securely.
	<input type="radio"/> Trouble in electromagnetic or electronic circuit parts	Replace the faulty parts.
2)	Decline of fuel pump function	Replace the fuel pump.
3)	Clogged fuel filter	Replace the fuel filter. Clean or replace the fuel tank if necessary.
4)	Clogged or bent fuel pipe or hose	Clean, correct or replace fuel pipe or hose.
5)	Air is mixed in fuel system.	Inspect and retighten each connection part.
6)	Clogged or bent air breather tube or pipe.	Clean, correct or replace the air breather tube or pipe.
7)	Damaged diaphragm of pressure regulator	Replace.
<b>2. Leakage or blow out of fuel</b>		
1)	Loose joints of the fuel pipe	Retighten.
2)	Cracked fuel pipe, hose and fuel tank	Replace.
3)	Defective welding part on the fuel tank	Replace.
4)	Clogged or bent air breather tube or air vent tube	Clean, correct or replace the air breather tube or air vent tube.
<b>3. Gasoline smell inside of compartment</b>		
1)	Loose joints at air breather tube, air vent tube and fuel filler pipe	Retighten.
2)	Problem in tightening of the fuel saucer gasket air	Correct or replace the gasket.
3)	Inoperative fuel pump modulator or circuit	Replace.
<b>4. Defective fuel meter indicator</b>		
1)	Defective operation of fuel level sensor	Replace.
2)	Defective operation of fuel meter	Replace.
<b>5. Noise</b>		
1)	Large operation noise or vibration of fuel pump	Replace.

#### NOTE:

- When the vehicle is left unattended for an extended period of time, water may accumulate in the fuel tank. Fill fuel fully to prevent the problem.
- In snow-covered areas, mountainous areas, skiing areas, etc. where ambient temperatures drop to 0°C (32°F) or less throughout the winter season, use a water removing agent in the fuel system to prevent freezing fuel system and accumulating water.
- When water is accumulated in fuel filter, fill the water removing agent in the fuel tank.
- Before using water removing agent, follow the cautions noted on the bottle.

# EMISSION CONTROL (AUX. EMISSION CONTROL DEVICES)

# ***EC(H4DOTC)***

---

	Page
1. General Description .....	2
2. Front Catalytic Converter .....	5
3. Rear Catalytic Converter .....	6
4. Canister .....	7
5. Purge Control Solenoid Valve .....	11
6. Fuel Level Sensor .....	15
7. Fuel Temperature Sensor .....	16
8. Fuel Sub Level Sensor .....	17
9. Fuel Tank Pressure Sensor .....	18
10. Pressure Control Solenoid Valve .....	19
11. Drain Filter .....	20
12. Shut Valve .....	21
13. Drain Valve .....	22
14. PCV Hose Assembly .....	23
15. Secondary Air Pump .....	24
16. Secondary Air Combination Valve .....	25