

# STEERING Warning Light

POWER ASSISTED SYSTEM (POWER STEERING) (DIAGNOSTICS)

## 10. STEERING Warning Light

### A: STEERING WARNING LIGHT DOES NOT COME ON

#### 1. POWER STEERING ASSIST ENABLED

##### DETECTING CONDITION:

- Defective combination meter
- Defective harness

##### TROUBLE SYMPTOM:

When the ignition switch is turned to ON (engine OFF), the steering warning light does not illuminate.

##### NOTE:

It is operating normally if the warning light illuminates when the ignition switch is turned to ON (engine OFF), and turns off approximately two seconds after engine start.

Step	Check	Yes	No
1 <b>CHECK ILLUMINATION OF OTHER LIGHTS.</b> Turn the ignition switch to ON. (engine OFF)	Do other warning lights illuminate?	Go to step 2.	Check the combination meter. <Ref. to IDI-9, INSPECTION, Combination Meter System.>
2 <b>CHECK LAN SYSTEM.</b> Perform the diagnosis for LAN system using the Subaru Select Monitor. <Ref. to LAN(diag)-2, Basic Diagnostic Procedure.>	Is DTC related to CAN displayed?	Perform the diagnosis according to DTC. <Ref. to LAN(diag)-43, List of Diagnostic Trouble Code (DTC).>	Go to step 3.
3 <b>CHECK COMBINATION METER.</b> Perform the self-diagnosis of combination meter. <Ref. to IDI-6, SELF-DIAGNOSIS DISPLAY MODE, OPERATION, Combination Meter System.>	Is the self diagnosis normal?	The combination meter is normal.	Check the combination meter. <Ref. to IDI-9, INSPECTION, Combination Meter System.>

# STEERING Warning Light

POWER ASSISTED SYSTEM (POWER STEERING) (DIAGNOSTICS)

## 2. POWER STEERING ASSIST DISABLED

### DETECTING CONDITION:

CAN communication error (Engine rpm signal not received)

### TROUBLE SYMPTOM:

The steering warning light is normal but there is no power steering assist (steering feels heavy).

#### NOTE:

- Power steering assist is not started unless an ignition switch ON signal or engine speed signal is input.
- In any of the following cases, the power steering assist is limited and steering wheel operation may become heavy.

If the steering wheel is held to an end for a long time, or the steering wheel turning to right and left at slow speed is repeated during parking, the assist limitation (overheat protection control) may operate to prevent failures by overheat.

In this case, by stopping the engine for approx. 10 minutes for cooling, the assist will start operating. While assist limitation (overheat protection control) is in active, "Assist limitation" is displayed in the «EPS operating condition» in the Subaru Select Monitor "Current Data Display & Save".

- History can be confirmed on «Overheating protection intervention history» or «IGN count from overheating protection» of "Current Data Display & Save".
- The overheat protection control system is normal operation, therefore, the steering warning light will not come on and there will be no DTC displayed.
- If the power steering system connector is disconnected while cooling under the overheat protection control, different DTC may be recorded. If there is no DTC and assist limitation is in active, stop the engine for approx. 10 minutes for cooling.

Step	Check	Yes	No
1 <b>CHECK CURRENT DATA.</b> Using the Subaru Select Monitor, display «EPS operating condition». <Ref. to PS(diag)-13, READ CURRENT DATA, OPERATION, Subaru Select Monitor.>	Is "Assist limitation" displayed?	Stop the engine for approx. 10 minutes, and cool down the power steering control module. After cooling down, perform the step 1 again.	Go to step 2.
2 <b>CHECK DTC.</b> Read the DTC of the power steering control module using Subaru Select Monitor. <Ref. to PS(diag)-17, Read Diagnostic Trouble Code (DTC).>	Is DTC displayed?	Perform the diagnosis according to DTC. <Ref. to PS(diag)-23, List of Diagnostic Trouble Code (DTC).>	Go to step 3.
3 <b>CHECK CURRENT DATA.</b> 1) Using the Subaru Select Monitor, display the current data «Torque sensor main output» and «Torque sensor sub output». 2) Move the steering wheel to the left and right.	Do the torque sensor values change?	Go to step 4.	Check the torque sensor circuit. <Ref. to PS(diag)-25, DTC C2511 TORQUE SENSOR FAILURE 1 (MAIN), Diagnostic Procedure with Diagnostic Trouble Code (DTC).>
4 <b>CHECK CURRENT DATA.</b> 1) Start the engine. 2) Using the Subaru Select Monitor, display «Engine Speed».	Is the engine speed signal the same as that in the combination meter?	Replace the power steering control module. <Ref. to PS-41, REMOVAL, Power Steering Control Module.>	Check the CAN communication. <Ref. to LAN(diag)-2, Basic Diagnostic Procedure.>

# STEERING Warning Light

## POWER ASSISTED SYSTEM (POWER STEERING) (DIAGNOSTICS)

### B: STEERING WARNING LIGHT DOES NOT GO OFF

#### DETECTING CONDITION:

- Defective combination meter
- Open circuit of harness

#### TROUBLE SYMPTOM:

When starting the engine, the steering warning light continues to illuminate.

Step	Check	Yes	No
<b>1 CHECK DTC.</b> Read the DTC of the power steering control module using the Subaru Select Monitor. <Ref. to PS(diag)-17, Read Diagnostic Trouble Code (DTC).>	Is DTC displayed?	Perform the diagnosis according to DTC. <Ref. to PS(diag)-23, List of Diagnostic Trouble Code (DTC).>	Go to step <b>2</b> .
<b>2 CHECK LAN SYSTEM.</b> Perform the diagnosis for LAN system using the Subaru Select Monitor. <Ref. to LAN(diag)-2, Basic Diagnostic Procedure.>	Is a DTC related to CAN detected?	Perform the diagnosis according to DTC. <Ref. to LAN(diag)-43, List of Diagnostic Trouble Code (DTC).>	Check the combination meter. <Ref. to IDI-9, INSPECTION, Combination Meter System.>