

4. Variator Chain Break-in

A: GENERAL DESCRIPTION

Perform Variator Chain Break-in when the following work has been performed.

- Variator chain replacement
- Primary pulley and secondary pulley replacement

B: PROCEDURE

NOTE:

- During variator chain break-in, VDC warning light illuminate because of the difference between the vehicle speed value and G sensor value. This is not a malfunction. If the warning light illuminates, clear the VDC memory after the variator chain break-in is finished. <Ref. to VDC(diag)-23, Clear Memory Mode.>
- If the above malfunction code is detected during variator chain break-in, the system enters into fail mode, and the vehicle shows symptom such as engine speed rapid increases even if the accelerator pedal is gradually depressed.

1) Lift up the vehicle.

CAUTION:

Lift up the vehicle until the tire bottom is 0.3 m (0.98 ft) or more above the ground.

- 2) Shift the select lever to "P" or "N" range.
- 3) Apply the parking brake.
- 4) Connect the Subaru Select Monitor to data link connector.
- 5) Idle the engine to raise the CVTF temperature to 40 — 50°C (104 — 122°F) displayed on the Subaru Select Monitor.

NOTE:

When CVTF temperature does not rise easily or if you want to rise CVTF temperature faster, maintain the engine speed within 2,000 — 2,500 r/min at "P" or "N" range to raise the CVTF temperature.

- 6) With the select lever in "P" or "N" range, increase the engine speed to 3,000 — 3,500 r/min from the idling condition, and maintain the speed for approximately five seconds, then release the accelerator pedal.
- 7) Depress the accelerator pedal gradually again from idling condition to increase the engine speed to 3,000 — 3,500 r/min, maintain the speed for approximately five seconds, then release the accelerator pedal.
- 8) Release the parking brake.
- 9) Shift the select lever into manual mode and set to 1st.
- 10) Depress the accelerator pedal gradually, and increase the engine speed to 5,300 r/min from engine idling condition.

NOTE:

Increase the engine speed while taking care that the engine speed does not become too high.

- 11) Release the accelerator pedal to fully closed position to lower the engine speed to 4,000 r/min.
- 12) Depress the accelerator pedal gradually again, and increase the engine speed to 5,300 r/min.
- 13) Repeat the steps 11) and 12) for 40 times.
- 14) Release the accelerator pedal to return the engine speed to idling.
- 15) Shift the select lever to "P" range, and then turn the engine to OFF.