

6. Diagnostics with Phenomenon

A: DIAGNOSTIC PROCEDURE WITH PHENOMENON

Phenomenon		Check item	Index
1	Cruise control main switch is not turned to ON. (Cruise indicator light does not illuminate.) Or cruise control is cancelled without operating the cruise control command switch.	(1) Perform cruise cancel conditions diagnosis. (2) Perform the real-time diagnosis. (3) Check the cruise control command switch. (4) Check the cruise indicator light.	Perform the diagnosis according to displayed cancel code. Check the input signal of cruise control system. <Ref. to CC(diag)-13, 11, Diagnostic Procedure with Cancel Code.> <Ref. to CC(diag)-10, CHECK CRUISE INDICATOR LIGHT AND CRUISE SET INDICATOR LIGHT, Diagnostics with Phenomenon.>
2	Cruise control cannot be set. Or cruise control is cancelled without releasing operation.	(1) Perform cruise cancel conditions diagnosis. (2) Perform the real-time diagnosis. (3) Check the cruise control command switch. (4) Check stop light switch and brake switch. (5) Check the neutral position switch. (6) Check vehicle speed sensor.	Perform the diagnosis according to displayed cancel code. Check the input signal of cruise control system. <Ref. to CC(diag)-13, 11, Diagnostic Procedure with Cancel Code.> <Ref. to BR-37, Brake Pedal.> <Ref. to CC(diag)-15, 12, Diagnostic Procedure with Cancel Code.> <Ref. to CC(diag)-17, 14, Diagnostic Procedure with Cancel Code.> <Ref. to CC(diag)-20, 62, Diagnostic Procedure with Cancel Code.> <Ref. to CC(diag)-19, 22, Diagnostic Procedure with Cancel Code.>
3	Cruise set indicator light does not illuminate.	Check the cruise set indicator light.	<Ref. to CC(diag)-10, CHECK CRUISE INDICATOR LIGHT AND CRUISE SET INDICATOR LIGHT, Diagnostics with Phenomenon.>
4	Vehicle speed is not held within set speed ± 3 km/h (± 2 MPH).	Check the vehicle speed sensor.	<Ref. to CC(diag)-19, 22, Diagnostic Procedure with Cancel Code.>
5	Vehicle speed does not increase or does not return to set speed after RESUME/ACCEL switch has been pressed.	(1) Perform the real-time diagnosis. (2) Check the RESUME/ACCEL switch.	Check the input signal of cruise control system. <Ref. to CC(diag)-13, 11, Diagnostic Procedure with Cancel Code.>
6	Vehicle speed does not decrease after SET/COAST switch has been pressed.	(1) Perform the real-time diagnosis. (2) Check the SET/COAST switch.	Check the input signal of cruise control system. <Ref. to CC(diag)-13, 11, Diagnostic Procedure with Cancel Code.>
7	Cruise control is not released after CANCEL switch has been pressed.	(1) Perform the real-time diagnosis. (2) Check the CANCEL switch.	Check the input signal of cruise control system. <Ref. to CC(diag)-13, 11, Diagnostic Procedure with Cancel Code.>
8	Cruise control is not released after brake pedal has been depressed.	(1) Perform the real-time diagnosis. (2) Check stop light switch and brake switch.	Check the input signal of cruise control system. <Ref. to CC(diag)-15, 12, Diagnostic Procedure with Cancel Code.> <Ref. to BR-38, INSTALLATION, Stop Light Switch.>
9	Cruise control is not released after shifting to the neutral position.	(1) Perform the real-time diagnosis. (2) Check the neutral position switch.	Check the input signal of cruise control system. <Ref. to CC(diag)-17, 14, Diagnostic Procedure with Cancel Code.>

Diagnostics with Phenomenon

CRUISE CONTROL SYSTEM (DIAGNOSTICS)

B: CHECK CRUISE INDICATOR LIGHT AND CRUISE SET INDICATOR LIGHT

TROUBLE SYMPTOM:

Cruise control can be set, but the cruise indicator light and cruise set indicator light do not illuminate.

Step	Check	Yes	No
1 CHECK CRUISE INDICATOR LIGHT AND CRUISE SET INDICATOR LIGHT. 1) Perform the self-diagnosis of combination meter. <Ref. to IDI-4, SELF-DIAGNOSIS, INSPECTION, Combination Meter System.> 2) Check the cruise indicator light and cruise set indicator light if they illuminate.	Do the cruise indicator light and cruise set indicator light illuminate?	Go to step 2 .	Replace the meter case assembly. <Ref. to IDI-11, Combination Meter.>
2 CHECK DTC OF LAN COMMUNICATION CIRCUIT. 1) Complete self-diagnosis, and turn the ignition switch to ON again. 2) Read the DTC of body integrated unit using Subaru Select Monitor.	Is DTC of LAN system displayed?	Check the LAN communication circuit. <Ref. to LAN(diag)-2, Basic Diagnostic Procedure.>	Replace the ECM. <Ref. to FU(H6DO)-51, Engine Control Module (ECM).>