

BODY ELECTRICAL

SERVICE DATA

SS0B0-08

SPEEDOMETER (ON-VEHICLE)	
Standard indication (mph) Europe Models	Allowable range (mph)
20	20 – 24.5
40	40 – 46.5
60	60 – 68.5
80	80 – 90.5
100	100 – 112.5
Standard indication (km/h) Europe Models	Allowable range (km/h)
20	20 – 26
40	40 – 48
60	60 – 70
80	80 – 92
100	100 – 114
120	120 – 136
140	140 – 158
160	160 – 180
Standard indication (km/h) Australia	Allowable range (km/h)
40	36 – 44
60	54 – 66
80	72 – 88
100	90 – 110
120	108 – 132
140	126 – 154
160	144 – 176
TACHOMETER (ON-VEHICLE)/ DC 13.5 V 25 °C at (77 °F)	
Standard indication	Allowable range
700	700 – 770
1,000	900 – 1,100
2,000	1,850 – 2,150
3,000	2,800 – 3,200
4,000	3,800 – 4,200
5,000	4,800 – 5,200
6,000	5,800 – 6,200
7,000	6,800 – 7,200
FUEL SENDER GAUGE	
Float position mm (in.)	Resistance (Ω)
F: Approx. 75.9 (2.99)	Approx. 3.0
1/2: Approx. 17.2 (0.68)	Approx. 31.6
E: Approx. 50.8 (2.00)	Approx. 110.0
ENGINE COOLANT TEMPERATURE SENDER GAUGE (Resistance)	
Temperature °C (°F)	Resistance (Ω)
50 (122.0)	160 – 240
120 (248.0)	17.1 – 21.2