



Technical Service BULLETIN

August 19, 2003

Title:

SPARE TIRE CARRIER OPERATION

Models:

'91 – '04 Land Cruiser, '96 – '04 4Runner & Tacoma, '98 – '04 Sienna, '00 – '04 Tundra, '01 – '04 Sequoia

PG005-03

PRODUCT GENERAL INFORMATION

Introduction The spare tire carrier may become damaged if an impact wrench or any other type of power tool is used to raise or lower the spare tire. The owner's manual, as well as a label near the drive nut, warns against the usage of an impact wrench or other power tools.

- Applicable Vehicles**
- 1991 – 2004 model year **Land Cruiser** vehicles.
 - 1996 – 2004 model year **4Runner & Tacoma** vehicles.
 - 1998 – 2004 model year **Sienna** vehicles.
 - 2000 – 2004 model year **Tundra** vehicles.
 - 2001 – 2004 model year **Sequoia** vehicles.

- Operation Procedure**
- Refer to vehicle's owner's manual for vehicle specific instructions.
1. Locate the drive nut for the spare tire carrier. Refer to the vehicle's owner's manual for specific location.
 2. Using the hub nut box wrench from the vehicle's tire tools kit, lower the spare tire to the ground.
 3. Remove the tire from the carrier.
 4. Installation of the spare tire is the reverse of removal.

Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
N/A	Not Applicable to Warranty	–	–	–	–

