

## LUBRICANT

Item	Capacity	Application
Front drive shaft		
Outboard joint grease (Color = Black)	205 – 225 g (7.23 – 7.94 oz.)	
Inboard joint grease (Color = Black)	190 – 210 g (6.70 – 7.41 oz.)	
Front differential Differential oil	1.15 liters (1.22 US qts., 1.01 Imp. qts.)	Hypoid gear oil API GL-5 SAE 75W-90
Rear differential (Standard type) Differential oil 2WD		
Standard Cab and Access Cab:	3.80 liters (4.02 US qts., 3.34 Imp. qts.)	Hypoid gear oil API GL-5
Double Cab	4.00 liters (4.23 US qts., 3.52 Imp. qts.)	Above -18°C (0°F) SAE 90
4WD		Below -18°C (0°F) SAE 80W or 80W-90
Standard Cab and Access Cab:	3.50 liters (3.70 US qts., 3.08 Imp. qts.)	
Double Cab	4.00 liters (4.23 US qts., 3.52 Imp. qts.)	
Rear differential (LSD type) Differential oil 2WD		
Standard Cab and Access Cab:	3.15 liters (3.33 US qts., 2.77 Imp. qts.)	Hypoid gear oil for LSD API GL-5
Double Cab	3.35 liters (3.54 US qts., 2.95 Imp. qts.)	Above -18°C (0°F) SAE 90
4WD		Below -18°C (0°F) SAE 80W or 80W-90
Standard Cab and Access Cab:	2.85 liters (3.01 US qts., 2.51 Imp. qts.)	
Double Cab	3.35 liters (3.54 US qts., 2.95 Imp. qts.)	